DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM-17807

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

Gas Well [X] Gas Well [ ] Other

Name of Operator: Siete Oil & Gas Corporation

Address of Operator: P.O. Box 2523 Roswell, NM 88202-2523

Location of Well (Report location clearly and in accordance with any State requirements.): 330' FSL & 2310' FWL, SE¼SW¼, Unit Letter N

Lease Name: Quanah Federal

Well No.: 1

Field and Pool, or Wildcat: ~~Young Wolfcamp~~ Querecho Plain Upper BS

Sec., T., R., M., or Blk. and Survey or Area: Sec. 14: T18S, R32E

Permit No.: 30-025-30445

Elevations (Show whether DF, RT, GR, etc.): 3792' GR

County or Parish: Lea

State: NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

Notice of Intention to:				Subsequent Report of:			
Test Water Shut-off		Pull or Alter Casing		Water Shut-off		Repairing Well	
Fracture Treat		Multiple Complete		Fracture Treatment	X	Altering Casing	
Shoot or Acidize		Abandon*		Shooting or Acidizing	X	Abandonment*	
Repair Well		Change Plans		(Other)			
(Other)							

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/18/88 RU Schlumberger, set CIBP @ 10200', perf interval 10008'-10029' w/15 perforations, TIH w/tbg & pkr, spot 2 bbls acid across perfs, set pkr @ 9935', acidized w/1000 gal 7½% HCl, formation broke @ 4120 PSI, AIR-3 BPM, AIP-3000 PSI, balled out to 5130 PSI, max pump-in pressure-4530 PSI before ball out, surge balls & finish flush @ 3 BPM @ 3000 PSI, ISIP-2670, @ 5 min-2590, @ 10 min-2590, @ 15 min-2590, SI 1 hr, flowback 55 BF, begin swabbing.

10/21/88 RU Dowell Schlumberger & frac w/38,000 gal 40# XL, 2000# 100 mesh, 90,000# 16/30 ottwa sand, 23,760# 16/30 resin-coated sand, AIR-16 BPM, AIP-3300, max-3470, FPIP-3420, ISIP-3080, @ 5 min-3070, @ 10 min-3060, @ 15 min-3050, SION, begin swabbing tomorrow.

RECEIVED
NOV 4 11 33 AM '88
CARLSBAD AREA
BLM

I hereby certify that the foregoing is true and correct

Signed: Cathy Batley Title: Drilling/Production Secretary Date: 10/27/88

(This space for Federal or State office use)

Approved by: Title: Date:

Conditions of Approval, if any:

ACCEPTED FOR RECORD
NOV 1 8 1988
SJS
CARLSBAD, NEW MEXICO

*See Instructions on Reverse Side