

WRS COMPLETION REPORT
 REISSUES SEC 13 TWP 18S RGE 32E
 PI# 30-T-0004 05/22/89 30-025-30462-0000 PAGE 1

NMEX LEA * 330FSL 330FWL SEC SW SW
 STATE COUNTY FOOTAGE SPOT
 MEWBOURNE OIL D DO
 OPERATOR WELL CLASS INIT FIN

1 FEDERAL "M"
 WELL NO LEASE NAME
 3829KB 3806GR QUERECHO PLAINS
 OPER ELEV FIELD POOL AREA

API 30-025-30462-0000
 PERMIT OR WELL ID. NO
 02/18/1989 03/24/1989 ROTARY OIL
 SPUD DATE COMP DATE TYPE TOOL STATUS

9500 BONE SPG W E K DRLG 1 RIG SUB 20
 PROJ DEPTH PROJ FORM CONTRACTOR
 DTD 8670 PB 8596 FM/TD BONE SP2
 DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM I.D.

LOCATION DESCRIPTION

14 MI SW BUCKEYE, NM

CASING/LINER DATA

CSG 13 3/8 @ 450 W/ 400 SACKS
 CSG 8 5/8 @ 4332 W/ 1220 SACKS
 CSG 5 1/2 @ 8670 W/ 1425 SACKS

TUBING DATA

TBG 2 7/8 AT 8299

INITIAL POTENTIAL

IPF 250BOPD 162 MCFD 24/64CK 24HRS
 BN SP UP PERF W/ 58/IT 8424- 8514 GROSS
 TP 80
 GTY 42.0 GOR 648
 FIELD /RESERVOIR
 /BONE SPRING
 FCP PKR

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	SALT			2586 1243
LOG	QUEEN		3992 -163	
LOG	PENROSE		4249 -420	
LOG	SN ANDRS		4808 -979	
LOG	DELAWARE		5304 -1475	

CONTINUED IC# 300257032788

REISSUES SEC 13 TWP 18S RGE 32E
PI# 30-T-0004 05/22/89 30-025-30462-0000 PAGE 2

MEWBOURNE OIL D DO
1 FEDERAL "M"

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	BONE SPG		6838 -3009	
LOG	BONE SP1		8318 -4489	
LOG	BONE SP2		8604 -4775	

SUBSEA MEASUREMENTS FROM KB

PRODUCTION TEST DATA

BONE SPG PERF W/ 58/IT 8424- 8514 GROSS
PERF 8424- 8434 8453- 8484 8486- 8494 8509- 8514
ACID 8424- 8514 5900GALS
SWFR 8424- 8514 70000GALS 105000LBS SAND ADDTVGELA
2% KCL 78750 LBS 20/40 OTTAWA
26250 LBS 20/40 RESIN COATED

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS	DLL	SDBL	DSN
------	-----	------	-----

DRILLING PROGRESS DETAILS

MEWBOURNE OIL
701 S CECIL
HOBBS, NM 88240
505-393-5905
08/12 LOC/1988/
02/23 DRLG 3278
03/02 DRLG 5265
03/09 DRLG 8097
03/15 8670 TD, WOCT
03/15 DEVIATION SURVEYS @ 450 (1/4 DEG), 939 (1 DEG),
1439 (1 1/4 DEG), 1930 (1 1/2 DEG), 2454 (1 DEG),
2945 (1 1/4 DEG), 3438 (1 DEG), 3815 (1 DEG),
4332 (1 1/4 DEG), 4849 (1 DEG), 5315 (1 DEG),
5812 (1 1/4 DEG), 6098 (1 DEG), 6594 (1 1/4 DEG),
6971 (1 DEG), 7440 (1 1/4 DEG), 7816 (3/4 DEG),
8345 (3/4 DEG), 8670 (1/2 DEG)
03/22 8670 TD, PB 8596, SWBG
03/30 8670 TD, PB 8596, WOCT
TD REACHED 03/13/89 RIG REL 03/13/89
04/11 8670 TD, PB 8596
COMP 3/24/89, IPF 250 BO, 162 MCFGPD, 165

CONTINUED

REISSUES SEC 13 TWP 18S RGE 32E
PI# 30-T-0004 05/22/89 30-025-30462-0000 PAGE 3

MEWBOURNE OIL
1

FEDERAL "M"

D DO

DRILLING PROGRESS DETAILS

05/18
BLW, 24/64 CK, GOR 648,
GTY 42, FTP 80, FCP PKR
PROD ZONE - BONE SPRING 8424-8514
NO CORES OR DSTS RPTD
REISSUED TO CORRECT FM @ TD, IP & ADD
TBG, TREATMENT, LOG TOPS, LOGS RUN
REPLACEMENT FOR CT ISSUED 4/17/89