

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Aramis, NM 88210

DISTRICT III
1000 Rio Arriba Rd., Alamogordo, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30476
1. Indicate Type of Lease STATE ☒ FREE ☐
6. State Oil & Gas Lease No. 8-155
7. Lease Name or Unit Agreement Name New Mexico "O" State NCT-1
8. Well No. 29
9. Pool name or Wildcat Vacuum Glorieta

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL ☒ GAS ☐ OTHER ☐	2. Name of Operator Texaco Producing Inc.
3. Address of Operator P.O. Box 728, Hobbs, New Mexico 88240	4. Well Location Unit Letter N : 990 Feet From The South Line and 2310 Feet From The West Line Section 36 Township 17-S Range 34-E N44PM Lea County

10. Elevation (Show whether D.F., RKS, RT, GR, etc.) 3984 GR
--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: COMPLETION ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 6270'
16" 75' K-55 CASING SET AT 425'
11-3/4" 42' H-40 CASING SET AT 1571'
8-5/8" 32' S-80, K-55 CASING SET AT 4843'
5-1/2" 15.5' K-55 CASING SET AT 6270'

1. MIRU 4-26-89. Install and test BOP. Clean out with 4-3/4" bit to 6180'. Tested 5-1/2" casing to 1500 psi for 30 minutes. Tested OK.

2. Run GR/CNL/CCL Correlation log from 6175' to 4150'.

3. Perforate through tubing 2 JSPF at 6103-6112, 6115-6116, 6123-6125, 6130-6132' (Total 18 intervals, 36 shots). Swab test.

(OVER)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Johnnie Clay* for H.F. Smith TITLE Area Superintendent DATE 5/8/89

TITLE OR PRINT NAME H. F. Smith TELEPHONE NO. 393-4031

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON, DISTRICT I SUPERVISOR.

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAY 8 1989

4. Acidize with 2500 gals 15% NEFE, 30,000 SCF Nitrogen, and 60 ball sealers.
Max TP 2400 psi, min TP 800 psi, AIR 1.8 BPM, ISIP 1600 psi. Swab.
5. Pump test. On 24 hour OPT 5-4-89, pumped 198 BO, 10 BW, 202 MCF, GOR 1020, gravity 38.6 from Glorieta perforations 6103'-6132'.

RECEIVED

MAY 8 1989

OCD
HOBBS OFFICE