		L CONSERVA	TION DIVISION	
DISTRIBUTION		P. O. BO		Form C-103
SANTA PE			V MEXICO 87501	Revised 10-1-78
FILE				Sa. Indicate Type of Louse
LAND OFFICE				State Fee X
OPERATOR			•	5. State Oll 6 Gas Lease No.
(DO NOT USE THIS	SUNDRY NOTICES	AND REPORTS ON	WELLS BACH TO A DIFFERENT RESERVOIR. CH FROPOSALS.)	
U	E "APPLICATION FOR PERMIT -	** (FOAM C+101) FOA SU	CH PROPOSALS.)	7. Unit Agreement Name
	LL OTHER-			7. Onte Agreement Name
me of Operator				8. Farm or Lease Hame
Pennzoil Exploration & Production Company				PRICE FAMILY TRUST
P. O. Drawer 1828 - Midland, Texas 79702-1828				9. Well No.
Location of Well				2
UNIT LETTER N 900 PEET FROM THE South LINE AND 1750 PEET FROM				10. Field and Pool, or Wildcat
West LINE, SECTION TOWNSHIP 17-S 37-E .				
15. Elevation (Show whether DF, RT, GR, etc.)				12. County
3737.5 GR - 3762.9 RKB				LEA ()))))))
	Check Appropriate E	Box To Indicate N	lature of Notice, Report or	Other Data
NOT	ICE OF INTENTION TO) :		ENT REPORT OF:
ORM REMEDIAL WORK		PLUG AND ABANDON	AEMEDIAL WORK	<u> </u>
ORARILY ABANDON	7		COMMENCE DRILLING OPHS. X	ALTERING CASING
		CHANGE PLANS	CASING TEST AND CEMENT JOB	PLUG AND ABANDONMENT
			OTHER	[]
HER				
escribe Proposed or C prkj SEE RULE 1103	ompleted Operations (Clearly	state all pertinent dett	ails, and give pertinent dates, includ	ling estimated date of starting any proposed
· · · · · · · · · · · · · · · · · · ·				
· · · · · · · · · · · · · · · · · · ·			L ails, and give persinent dates, includ cilling Company Rig #10	
<u>11/11/88</u> :	Moved in and rigg	ged up McVay Di	cilling Company Rig #10	
· · · · · · · · · · · · · · · · · · ·	Moved in and rigg Spudded 17-1/2" h	ged up McVay Dr nole at 10:30 A	rilling Company Rig #10 A.M. MST 11/11/88.).
<u>11/11/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4	ged up McVay D nole at 10:30 4 400' - Rigged u	cilling Company Rig #10 A.M. MST 11/11/88. up and ran 10 jts. of 1).
<u>11/11/88</u> :	Moved in and rigg Spudded 17-1/2" h Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' 5 -C- plus 2% (A.M. MST 11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/11/11/11/11/11/11/11/11/11/11/11/). 13-3/8", 48 $\#$, and cemented x = Plug down
<u>11/11/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' 5 -C- plus 2% (- Circulated 2	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim). 13-3/8", 48#, and cemented g - Plug down
<u>11/11/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' 5 -C- plus 2% (- Circulated 2	A.M. MST 11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/11/88. A.M. MST 11/11/11/11/11/11/11/11/11/11/11/11/11/). 13-3/8", 48#, and cemented g - Plug down
<u>11/11/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' 5 -C- plus 2% (- Circulated 2	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim). 13-3/8", 48#, and cemented g - Plug down
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees.	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees -	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t). 13-3/8", 48#, and cemented g - Plug down mate cement cemperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 0 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 Ve strength of cement). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 0 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 Ve strength of cement). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 0 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 Ve strength of cement). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 0 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 Ve strength of cement). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested nated compressi	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 0 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 Ve strength of cement). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim casing test 1500	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - 2 hrs Tested hated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t casing and BOP to 500 ve strength of cement ed drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - 2 hrs Tested nated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t casing and BOP to 500 ve strength of cement ed drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim casing test 1500	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested hated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 ave strength of cement ad drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement cemperature) psi for 30" - at time of
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim casing test 1500	ged up McVay Dr nole at 10:30 A 00' - Rigged u and set at 400' s -C- plus 2% (- Circulated 2 ce 65 degrees - chrs Tested hated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t casing and BOP to 500 ve strength of cement ed drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement emperature
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim casing test 1500	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400 s -C- plus 2% (- Circulated 2 ce 65 degrees - 2 hrs Tested hated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 ave strength of cement ad drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement cemperature) psi for 30" - at time of
<u>11/11/88</u> : <u>11/12/88</u> : <u>11/13/88</u> : <u>11/13/88</u> :	Moved in and rigg Spudded 17-1/2" H Drilled to T.D. 4 H-40 STC casing.a with 450 sx Class at 8:20 P.M. MST slurry temperatur 75 degrees. W.O.C. for 11-1/2 Held O.K Estim casing test 1500	ged up McVay Dr nole at 10:30 A 400' - Rigged u and set at 400 s -C- plus 2% (- Circulated 2 ce 65 degrees - 2 hrs Tested hated compressi psi - Commence	A.M. MST 11/11/88. ap and ran 10 jts. of 1 - Rigged up BJ Titan CaCl ₂ mixed at 14.8 ppg 20 sx to pit - Approxim - Estimated formation t 1 casing and BOP to 500 ave strength of cement ad drilling 11" hole.). 13-3/8", 48#, and cemented g - Plug down hate cement cemperature) psi for 30" - at time of

Contraction of the second seco

۰. **...**•