

Form 3160-5  
November 1983)  
Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Manzano Oil Corporation	8. FARM OR LEASE NAME Wynell Federal
3. ADDRESS OF OPERATOR P.O. Box 2107, Roswell, NM 88202-2107	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  2310' FSL & 660' FEL	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GM, etc.) 3667' GL
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 15, T19S, R33E
	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other) running casing	<input checked="" type="checkbox"/>
(Other)	<input type="checkbox"/>	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and notes pertinent to this work.)

7/8/89 Ran 107 jts (4201.64') 5-1/2" 23# N80 LT&C 8 rnd casing, 164 jts (7117.79') 5-1/2" 20# N80 LT&C 8 rnd casing, 59 jts (2385.92') 23# N80 LT&C 8 rnd casing with guide shoe, float collar & 20 centralizers. Set @ 13,700'. Cement with 1100 sacks Class H 50/50 pozmix with 5# salt & 4/10% Halide 22. PD @ 8:50 a.m. 7/9/89. PBD @ 13,660'. Estimated cement top @ 7500'.

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED Allen C. Williams TITLE Land/Drilling Secretary DATE 7/12/89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

JUL 21 1989

\*See Instructions on Reverse Side

SSS  
CARISBAD, NEW MEXICO