

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
P.O. BOX 1800
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Manzano Oil Corporation		8. FARM OR LEASE NAME Wynell Federal
3. ADDRESS OF OPERATOR P.O. Box 2107, Roswell, NM 88202-2107		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL & 660' FEL		10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 15, T19S, R33E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3667' GL		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Running casing</u> ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/03/89 Ran 26 jts (1130.29') 8-5/8" 32# S80 ST&C 8 rnd; 6 jts (190.28') 8-5/8" 32# K55 ST&C 8 rnd; 48 jts (2045.34') 8-5/8" 32# J55 ST&C 8 rnd; 39 jts (1638.02') 8-5/8" 24# J55 ST&C 8 rnd; 5 jts (205.22') 8-5/8" 32# J55 ST&C 8 rnd; 124 jts total (5209.15'). Set @ 5200' with float shoe, float collar and five centralizers. Cemented with 1400 sacks Halliburton lite, 15# salt, 1/4# floseal. Tail in with 700 sacks Class C 2% CaCl. Circulate 250 sacks. PD @ 10:40 a.m. 6/3/89. Test casing to 2500# held ok.

RECEIVED
JUL 3 9 01 AM '89
OIL & GAS
AREA

18. I hereby certify that the foregoing is true and correct

SIGNED <u>Allison H. Higgins</u>	TITLE <u>Land/Drilling Secretary</u>	DATE <u>June 30, 1989</u>
(This space for Federal or State office use)		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

*See Instructions on Reverse Side

RECEIVED

JUL 13 1989

OCD

HOBBS OFFICE