

RECEIVED
MAY 13 10 43 AM 1993
C.A.B.
APR 11UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTN. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1993, Roswell, NM 88201 1-505-623-6601

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 2310' FEL
SEC. 8, T-18S, R-32E

5. Lease Designation and Serial No.

NM-77315

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

AMOCO CP "8" FEDERAL # 2

9. API Well No.

30-025-30562

10. Field and Pool, or Exploratory Area

YOUNG GRAYBURG

11. County or Parish, State

LEA

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change in Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input checked="" type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other <u>OR P&A IF NOT COMMERCIAL</u>	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PRESENT PERFS: 4488-4703. 5' (OA). SET CIBP @ 4450' w/ 50' CMT. (NEW PBTD @ 4400').

PERFORATE PREMIER FROM 4240-50 AND ACIDIZE.


SWAB TO RECOVER LOAD ACID WATER. PUT ON PRODUCTION TO TEST.

IF NOT COMMERCIAL THEN P&A WELL AS FOLLOWS:

- 1 SET CIBP @ 4200' w/ 50 CMT ON TOP. TOC @ 2900'.
- 2 CUT CSG @ APPROX. 2650'. NOTE: INTERMEDIATE SHOE @ 2688'.
- 3 SPOT 100' CMT PLUG AT CUT OFF, (50' IN AND 50' OUT). THIS WILL ALSO BE SHOE PLUG.
- 4 SPOT 100' PLUG FROM 1135 TO 1035' (ACROSS RUSTLER @ 1082').
- 5 SPOT 100' PLUG FROM 471' TO 371'. (ACROSS SURFACE SHOE @ 421').
- 6 SPOT 50' PLUG TO SURFACE. INSTALL DRYHOLE MARKER AND CLEAN LOC.

14. I hereby certify that the foregoing is true and correct.

Signed



RAY F. NOKES

Title

PROD. MGR./ ENG.

Date 5/10/93

(This space for Federal or State office use)

Approved by

(ORIG. SGO.) JOE G. LARA

Title

M. T. C. E. U. M. ENGINEER

Date

JUN 14 1993

Conditions of approval, if any:

27 11 1992

27 11 1992

27 11 1992

RECEIVED

JUN 18 1993

GOD HOBBS
OFFICE