

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-30582

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

25694

7. Lease Name or Unit Agreement Name

J. R. Holt

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Texland Petroleum, Inc.

8. Well No. 2

3. Address of Operator
777 Main Street, Ste. 3200
Fort Worth, Tx. 76102

9. Pool name or Wildcat
Shipp Strawn

4. Well Location

Unit Letter C : 940 feet from the North line and 2210 feet from the West line

Section 2 Township 17S Range 37E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3760

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

Current PBTD 11,742'

1. Circulate hole with 9.5 ppg brine w/ 25# gel per barrel.
2. Spot 25sx Class C cement across to of Strawn (top perms 11,492') at 11,400 - 11,650'
3. Tag cement plug 11,400 - 11,650'
4. Spot 25sx Class C cement 8100' - 8350' to cover top of Tubbs @ 8229'
5. Spot 25sx Class C cement 4350' - 4600' across 8 5/8 casing shoe at 4450'
6. Tag cement plug 4350' - 4600'
7. Spot 25sx Class C cement 350' - 600' across 11 3/4 casing shoe @ 450'
8. Tag cement plug @ 350' - 600'
9. Spot 10sx Class C cement @ 100' to surface.
10. Cut off Wellhead and weld on steel plate with steel pipe marker.

→ SPOT 25SX PLUG TOP OF SALT F/2233' - 2133'

Well must be in compliance with Rule

202

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ann Burdette TITLE Regulatory Analyst

DATE 11/13/2001

Type or print name Ann Burdette

(This space for State use)

ORIGINAL SIGNED BY

GARY W. WINK

OFF FIELD REPRESENTATIVE II/STAFF MANAGER

Telephone No. (817)336-2751

MAR 05 2002

APPROVED BY Ann Burdette TITLE DATE

Conditions of approval, if any:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.