

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Siete Oil & Gas Corporation		8. FARM OR LEASE NAME Inca Federal	
3. ADDRESS OF OPERATOR P.O. Box 2523 Roswell, NM 88202-2523		9. WELL NO. 11	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 430' FNL & 330' FEL, NE $\frac{1}{4}$ NE $\frac{1}{4}$, Unit Letter A		10. FIELD AND POOL OR WILDCAT Wildcat Delaware	
14. PERMIT NO 30-025-30609		12. COUNTY OR PARISH Lea	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3781' GR		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5/27/89 TD 7 7/8" hole to 6500' @ 12:15 PM; RU Schlumberger & ran CNL/LDT & DLL?MSFL on interval 50'-6445', logger's TD @ 6478'.

5/28/89 RU Dowell and plugged well as follows:

plug #1 - set @ 6500' w/75 sxs HEII w/1% CaCl, wait 3 hrs, tag @ 6222'
plug #2 - set @ 5150'-5050' w/30 sxs HEII
plug #3 - set @ 4335'-4235' w/30 sxs HEII
plug #4 - set @ 3760'-3660' w/30 sxs HEII
plug #5 - set @ 3010'-2910' w/30 sxs HEII
plug #6 - set @ 2665'-2565' w/30 sxs HEII
plug #7 - set @ 2400'-2300' w/30 sxs HEII
plug #8 - set @ 1305' w/30 sxs HEII w/4% CaCl, wait 2 hrs, tag @ 1185'
plug #9 - set @ 445'-345' w/30 sxs HEII
plug #10 - set @ 35'-surface w/10 sxs HEII

Position P&A marker, released rig @ 1:00 AM on 5/29/89.

18. I hereby certify that the foregoing is true and correct

SIGNED

Cathy Batley

TITLE Drilling & Production Tech.

DATE 6/29/89

(This space for Federal or State office use)

APPROVED BY

Shirley J. Smith

FOR: CHIEF WELLS

TITLE

DATE

7-5-89

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side