

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department
OIL CONSERVATION DIVISION
P. O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-103
Revised 1-1-89

DISTRICT I
P. O. Box 1980, Hobbs, NM 88240

DISTRICT II
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	WELL API NO. 30-025-30617
2. Name of Operator Phillips Petroleum Company	5. Indicate Type of Lease STATE ☒ FEE ☐
3. Address of Operator 4001 Penbrook Street, Odessa, Texas 79762	6. State Oil & Gas Lease No. B-2317
4. Well Location Unit Letter <u>P</u> : <u>620</u> Feet From The <u>south</u> Line and <u>1250</u> Feet From The <u>east</u> Line Section <u>35</u> Township <u>17-S</u> Range <u>34-E</u> NMPM Lea County	7. Lease Name or Unit Agreement Name M. E. Hale
	8. Well No. 23
	9. Pool name or Wildcat Vacuum Gb/SA
10. Elevation (Show whether DP, RKB, RT, GR, etc.) 4018.5' GR (unprepared)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-20-89: Spud 17-1/2" hole at 9:00 AM.

6-24-89: TD'd 17-1/2" hole at 9:45 AM at 1570'. Set 13-3/8" 54.5# K-55 ST&C casing at 1567' w/1500 sx Class "C" cement w/2% CaCl. Circ 600 sx cement. WOC 19 1/2 hours. Tested pipe rams and casing to 2000 psi, held ok.

7-02-89: TD'd 7-7/8" hole at 5:00 AM. Ran DLL-MSDL-GR-Cal from TD at 4800' tp 3500'; CNL-LDT-GR-Cal from 4800'-3500' and CNL-GR-Cal from 3500' to surface. Set 5-1/2" 14# K-55 ST&C & J-55 ST&C casing at 4800' w/1600 sx Class "C" 65/35 Poz w/6% Bentonite, 5% salt plus 400 sx Class "C" neat. Bumped plug at 12:30 AM 7-03-89.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

See reverse side

SIGNATURE L. M. Sanders
TYPE OR PRINT NAME L. M. Sanders

TITLE Regulation & Proration DATE 7-03-89
Supervisor
TELEPHONE NO. 915/367-1488

(This space for State Use)
Eddie W. Seay

APPROVED BY Oil & Gas Inspector

TITLE _____ DATE JUL 07 1989

CONDITIONS OF APPROVAL, IF ANY:

Circ 382 sx cement. ND BOP, set 5-1/2" casing slips, cut casing and released rig at 2:30 AM.

Waiting on completion unit.