

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLI
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 53239	
2. NAME OF OPERATOR Enron Oil & Gas Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 2267, Midland, Texas 79702		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1750' FSL & 990' FEL		8. FARM OR LEASE NAME Shinnery 1 Federal	
14. PERMIT NO. 30-025-30627		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3905.7' GR		10. FIELD AND POOL, OR WILDCAT Young, North Bone Spring	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 1, T18S, R32E	
		12. COUNTY OR PARISH Lea	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF: 6-21-89

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) casing test & cement job

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

CORRECTIONS: 13-3/8" set at 657'
9-5/8" set at 2965'

7/4/89

Set 9311' of 5-1/2" 17# K-55 LT&C.

Cemented with 800 sx. C1 H lite + 10% A-5 + 0.7% FP-8 mixed at 12.7 ppg, yield 2.02 cuft/sx.; followed by 500 sx. C1 C + 0.1% R-3 mixed at 15.6 ppg. yield 1.17 cuft/sx.

30 min. pressure tested to 2000#-OK.

WOC - 18 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty Gildon

TITLE

Regulatory Analyst

DATE

7/7/89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 21 1989

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO