

DRILLING, WORKOVERS & PRODUCTION DATA

GERONIMO

Perfs

Geronimo Federal #1

Lea County, NM
TD: 10,564'
PBSD: 10,491'

7510-7666' (58 holes)(Delaware)
9617-651' (1 spf); 9704-750' (1 spf);
9852-10,002' (23 holes)(Bone Springs)

AFE/LW: B6840/05023-01
WI: 100%
13 3/8" @ 1298'
8 5/8" @ 3355'
5 1/2" @ 10,562'

AFE: \$35,000

OBJECTIVE: Commingle Bone Springs & Delaware

DATE: 10/13/97

MD: 10564 Progress: 0 DSS: 10 MW: 0.0 Visc: 0 WL: 0.00
DC: \$ 4840 CUM: \$ 49400

Activity:

Daily Details:

POOH W/58 JTS 2 7/8" 6.5# N-80 TBG, BULL DOG BAILER, 32 JTS 2 7/8" 6.5# N-80 TBG, FLOAT SUB, X-OVER SUB, 12' OF 4 1/2" WASH PIPE & 4 1/4" MILL SHOE. REC'D FRAC SAND & CEMENT. RIH W/4 1/4" BIT, FLOAT SUB, 4-3 1/2" DC'S, 32 JTS 2 7/8" 6.5# N-80 TBG, BULL DOG BAILER & 256 JTS 2 7/8" 6.5# N-80 TBG. TAGGED @ 9221'. PU POWER SWIVEL. DRLD 9' CMT & CIBP. RIH W/46 JTS 2 7/8" 6.5# N-80 TBG TO 10,237'. (ALL TBG ON LOC.) POOH W/90 JTS 2 7/8" 6.5# N-80 TBG. SECURED WELL; SDFN.

DATE: 10/14/97

MD: 10564 Progress: 0 DSS: 11 MW: 0.0 Visc: 0 WL: 0.00
DC: \$ 2420 CUM: \$ 51820

Activity:

Daily Details:

FINISHED POOH W/202 JTS 2 7/8" 6.5# N-80 TBG, BAILER, 32 JTS 2 7/8" 6.5# N-80 TBG, 4-3 1/2" DC'S, FLOAT SUB & 4 1/4" BIT. RIH W/2 7/8" BULL PLUG, 4' X 2 7/8" PERF SUB, 1 JTS 2 7/8" N-80 TBG, 2 7/8" API SEATING NIPPLE, 82 JTS 2 7/8" 6.5# N-80 TBG, 5 1/2" TBG ANCHOR & 281 JTS 2 7/8" JTS 6.5# N-80 TBG. ND BOP. SET TA & LANDED TBG W/11,000# TENSION. NU WELL HEAD. RIH W/1 1/4" X 8' SAND GUARD FILTER, 2 1/2" X 1 1/2" X 26' RHBC PUMP, 154-3/4" NORRIS 97 RODS & 75-7/8" NORRIS 97 RODS. SECURED WELL; SDFN.

DATE: 10/15/97

MD: 10564 Progress: 0 DSS: 12 MW: 0.0 Visc: 0 WL: 0.00
DC: \$ 1760 CUM: \$ 53580

Activity:

Daily Details:

FINISHED RIH W/PUMP & RODS. SPACED RODS OUT & HUNG ON. RDMO WOU.

Tubing Detail

	Length (')	Depth (')
Elevation	17.00	
241 jts 2 7/8" 6.5# N-80 tbg	7,450.29	17.00
2 7/8" x 5 1/2" tbg anchor	3.80	7,450.29
82 jts 2 7/8" 6.5# N-80 tbg	2,598.31	7,454.09
2 7/8" SN	1.10	10,052.40
1 jt 2 7/8" 6.5# N-80 tbg	31.23	10,053.50
4' x 2 7/8" perf sub w/bull plug	4.19	10,084.73
EOT		10,088.92
Rod Detail		
1 1/4"x26' polish rod		
6' x 1" pony rod		
79-1" rods		
167-7/8" rods		
154-3/4" rods		
2 1/2"x1 1/2"x26' RHBC		
1 1/4"x8' sand guard filter		

DATE: 10/16/97

DC: \$ 0 CUM: \$ 53580

Activity:

Daily Details:

F-20, FTP-300 PSI, 15 MCF, 11 BO, 174 BW, CP-10 PSI.

DATE: 10/17/97

DC: \$ 0 CUM: \$ 53580

Activity:

Daily Details:

F-24, FTP-200 PSI, 36 MCF, 77 BO, 144 BW, CP-12 PSI.