

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side) 68240

RECEIVED

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1. WELL TYPE
☒ OIL ☐ GAS ☐ OTHER

2. NAME OF OPERATOR

Mitchell Energy Corp.

3. ADDRESS OF OPERATOR

400 W. Illinois, Ste. 1000, Midland, Tx. 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 660' FWL (NW/NW)

14. PERMIT NO.

15. ELEVATION (show whether DS, RT, GR, etc.)

3576' GL

16.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER Casing

WATER SHUT-OFF

REPAIRING WELL

FRAC TREATMENT

MULTIPLE COMPLETION

FRAC TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDON

SHOOTING OR ACIDIZING

ABANDONMENT*

REPLUG WELL

CHANGE PLUG

(Other) Csg & Cmtg report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DES RPT. (SEE INSTRUCTIONS FOR COMPLETE OPERATION) (Check) State all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-

10-25-89

Moranco Rig #3 spudded @ 0730 hrs CDT. Drld 17½" hole to 1298' and cmtd 13 3/8" 54.5 # k-55 ST & C csg @ 1298' w/730 sx class "C" cmt + 4% gel + ¼ # / sx Cello flake + 2% Cacl₂ and 400 sx class "C" + 2% Cacl₂. PD @ 0230 hrs CDT 10-27-89. Circ 325 sx to surf.

10-30-89

Drld 12¼" hole to 3355' and cmtd 8 5/8" 32 # k-55 ST & C csg @ 3355' w/750 sx 65/35 class "C"/Poz + 6% gel + 5 # / sx salt + 0.5% D112 + ¼ # / sx celloflake and 300 sx class "C" + 1% cacl₂. PD @ 0630 hrs 10-30-89. Circ 45 sx to pit.

11-18-89

Drld 7 7/8" hole to 10564' and cmtd 5½" 17 # k-55 & N-80 LT & C csg @ 10562' w/725 sx class "H" + 0.75 gps D604 AM + 0.01 gps M-45 + 5 # / sx kolite. Est TOC @ 7200'. Opened DV tool @ 6390' and cmt 2nd stage w/500 sx 50/50 class H/poz + 2% gel + 0.5% D-65 + 4.5 # / sx salt + 5 # / sx kolite + 0.2% D-46. PD @ 1200 hrs CST 11-18-89. Est TOC @ 4800'. Released rig at 1600 hrs 11-18-89. WOCU.

18. I hereby certify that the foregoing is true and correct.

SIGNED

G.W. Tullio

TITLE Dist Drlg Mgr

DATE 11-21-89

(This space is for signature or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY