

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TR
(Other instructions
verse side)

CATE
OR re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-15917

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Laguna Deep Federal Uni

8. FARM OR LEASE NAME

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Undes E. Gem Morrow Ga

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26 T-19-S, R-33-E

12. COUNTY OR PARISH 13. STATE

Lea

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

3624.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

Completion Work

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

1/17 MI RU DIAMOND WS. NU BOP, PICK UP 4-3/4" BIT, PICKING UP 2-7/8" TBG, INCOMP. SDON. TOC @ 2900' by temp. survey
1/18 FIN W/2-7/8" TBG & BIT TO TOC @ 10,351'. TSTD 5-1/2" CSG & BOP TO 1500 PSI, OK. DRLD CMT 10,351-10,488' (DV TOOL).
DRLD DV TOOL. TSTD TO 1500 PSI, OK. SDON.
1-19 FIN W/4-3/4" BIT TO TOC @ 13,454'. DRLD CMT 13,454' TO FC @ 13,517'. DRLD FLOAT COLLAR & CMT TO 13,540' ETD.
CIRC HOLE CLEAN. POOH, INCOMP. SDON.
1-20 POOH W/BIT. RAN CNL-GR-CCL LOG FRM 13,522' LTD TO 11,500'. RIN W/2-7/8" TBG TO 13,450', INCOMP. SDON.
1/22 PICK UP TBG TO 13,450'. SPOT 500 GAL 10% ACETIC ACID FRM 13,326-12,809'. PU TO 13,104'. DISPLACED HOLE W/6% KCL PKR
FLUID. SDON.
1/24 FIN. R&L 422 JTS & 1 SUB (13,060') 2-7/8" 6.5# N-80 EUE 8RD "AB" MODIFIED NEW TBG @ 13,078'. STUNG INTO BAKER F-1 PKR
@ 13,078'. ALL TBG INTERNALLY TSTD TO 7000 PSI. NO BOP, NU TREE. DISPLACED TBG W/W2. LANDED TBG IN 13,000#
COMPRESSION. BLED TBG PRES FRM 4200-3500 PSI. TSTD 2-7/8" X 5-1/2" ANNULUS TO 1500 PSI, OK. PERF LWR MORROW W/2-1/8"
TBG GUN 4 SPF 13,312-26' (57 SHOTS). BLED PRES FRM 3500-10 PSI IN 3 HRS, 1-2' FLARE. SDON.

CONFIDENTIAL

18. I hereby certify that the foregoing is true and correct

SIGNED

Bahay Bayan

TITLE

Drig. Supt.

DATE

1-25-90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side