

Attachment to Form C-105

Greenhill Petroleum Corporation
 Lovington San Andres West Field
 West Lovington Unit Well No. 65
 April 1990

Item #26 - Perforation Record

<u>Interval</u>	<u>Size</u>	<u>Number</u>
4706 - 4721	.41	60
4761 - 4770	.41	36
4857 - 4872	.41	60
4989 - 4991	.41	8
4995 - 5006	.41	44
5008 - 5018	.41	40
5020 - 5023	.41	12
5025 - 5030	.41	20
5060 - 5065	.41	16
5070 - 5078	.41	16
5081 - 5088	.41	16
5092 - 5098	.41	16
5100 - 5110	.41	40
4998	.41	1 (squeeze perf)
5030	.41	1 (squeeze perf)

Item #27 - Acid, Shot, Fracture, Cement, Squeeze, Etc.

<u>Depth Interval</u>	<u>Amount and Kind Material Used</u>
5060-65, 5070-78, 5088-81, 5092-98, 5100-10	2720 gallons gelled 20% HCl NEFE acid
4998, 5030	40 sacks Class "C" cement w/2% CaCl
4989-91, 4995-5006, 5008-18, 5020-23, 5025-30	4600 gallons gelled 20% HCl NEFE acid
4857-72	2200 gallons gelled 20% HCl NEFE acid
4761-70	1450 gallons gelled 20% HCl NEFE acid
4706-21	3375 gallons gelled 20% HCl NEFE acid and 150 gallons 28% HCl NEFE acid