

Attachment to Form C-105

Greenhill Petroleum Corporation
Lovington San Andres West Field
West Lovington Unit Well No. 66
April 1990

Item #26 - Perforation Record

<u>Interval</u>	<u>Size</u>	<u>Number</u>
4709 - 4715	.41	24
4718 - 4720	.41	8
4722 - 4724	.41	8
4835 - 4839	.41	16
4848 - 4851	.41	12
4855 - 4858	.41	12
4864 - 4869	.41	20
4871 - 4873	.41	8
4926 - 4933	.41	28
4956 - 4966	.41	40
4968 - 4975	.41	28
5053 - 5062	.41	36

Item #27 - Acid, Shot, Fracture, Cement, Squeeze, Etc.

<u>Depth Interval</u>	<u>Amount and Kind Material Used</u>
5053-62	1500 gallons gelled 20% HCl NEFE acid
4956-66, 4968-75	2400 gallons gelled 20% HCl NEFE acid
4926-33	1050 gallons gelled 20% HCl NEFE acid and 300 gallons 28% HCl NEFE acid
4835-39, 4848-51, 4855-58, 4964-69, 4871-73	2900 gallons gelled 20% HCl NEFE acid and 170 gallons 28% HCl NEFE acid
4709-15, 4718-20, 4722-24	4500 gallons gelled 20% HCl NEFE acid