

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30714
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 548570
7. Lease Name or Unit Agreement Name NEW MEXICO "O" STATE NCT-1
8. Well No. 31
9. Pool name or Wildcat VACUUM VACUUM GLORIETA + BLINERY

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator TEXACO PRODUCING INC.	
3. Address of Operator P.O. Box 3109, MIDLAND, TEXAS 79702	
4. Well Location Unit Letter F : 1980 Feet From The WEST Line and 2310 Feet From The NORTH Line Section 36 Township 17-SOUTH Range 34-EAST NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-4002', KB-4015'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1) TD 11" Hole @ 5:00 PM 2-2-90. RAN 26 ft to 8 5/8", 32#, S-80, LTC, CSG. (1101') + 44 ft to 8 5/8", 32#, K-55, LTC, (1883') SET AT 3000'. FC @ 2917'.

2) WESTERN CEMENTED WITH 650 SX5 35/65 POZ CLASS 'H' W/ 6% GEL, 5% SALT, (12.8 ppg, 1.87 cmt/sk, 9.9 wt/sk) TAIL WITH 250 SX5 CLASS 'H' WITH 2% CaCl<sub>2</sub> (15.6 ppg, 1.19 cmt/sk, 5.2 wt/sk) Bump PLUG @ 2:45 PM 2-3-90 CIRC. 234 SX5.

3) NU BOP & TEST 3000# - OK WOC - 18 1/4 HOURS FROM 2:45 PM 2-3-90 TO 9:00 AM 2-3-90

4) TEST CASING 1500# 30 min W FROM 10:30 PM TO 11:00 PM 2-3-90

5) DRILLING 7 7/8" HOLE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE CP Gaslan TITLE Drilling SUPERINTENDENT DATE 2-12-90

TYPE OR PRINT NAME \_\_\_\_\_ TELEPHONE NO. \_\_\_\_\_

(This space for State Use)

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

FEB 15 1990