

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30715
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. 744880
7. Lease Name or Unit Agreement Name STATE "BA"
8. Well No. 11
9. Pool name or Wildcat VACUUM GLORIETA + VACUUM BLIVEBRY

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator TEXACO PRODUCING INC.	
3. Address of Operator P.O. Box 3109, MIDLAND, TEXAS 79702	
4. Well Location Unit Letter <u>D</u> : <u>989</u> Feet From The <u>WEST</u> Line and <u>660</u> Feet From The <u>NORTH</u> Line Section <u>36</u> Township <u>17 SOUTH</u> Range <u>34 EAST</u> NMPM <u>LEA</u> County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>GR-4006', RB-4018, KB-4019</u>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD. 6600'
T.D. 7/8" HOLE @ 4:30 PM 12-6-89. HALLIBURTON LOGGING SERVICES RAN GR-DIL-MSFL 6597'-3900'. SPECTRA GR-CNL-LDT 6597 to 3000, GR TO SURFACE.
12-7-89 - RAN 154 # to 5 1/2", 15.5 #, J-55, LT+C CSG. (6587') SET AT 6600', DV Tool @ 4978', WESTERN CEMENTED: 1ST STAGE: 330 SACKS CLASS 'H' WITH 1/4 # CELLOSEAL (15.6 ppg, 1.18, 5.2) PLUG DOWN @ 10:45 PM. OPEN DV Tool, CIRC 33 SACKS. 2ND STAGE: 625 SACKS 35/65 POZ CLASS 'H' WITH 69% GEL, 59% SALT, 1/4 # CELLOSEAL (12.8 ppg, 1.87, 9.9) Tail WITH 250 SACKS CLASS 'H' (15.6 ppg, 1.18, 5.2) PLUG DOWN @ 6:00 AM. CIRC. 185 SACKS. SET SLIPS, ND BOPs, Jct. TBG. 5900L.
RELEASED BASIN #10 @ 4:30 PM. 12-8-89 WOC - 72 HOURS +.
PREP TO COMPLETE

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham TITLE Drilling Superintendent DATE 12-14-89
(915)
TYPE OR PRINT NAME C.P. BASHAM TELEPHONE NO. 688-4620

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

DEC 20 1989