

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30715
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 744880
7. Lease Name or Unit Agreement Name STATE "BA"
8. Well No. 11
9. Pool name or Wildcat VACUUM GLORIETA + VACUUM BLINERBY

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator TEXACO PRODUCING INC.	
3. Address of Operator P.O. Box 3109, MIDLAND, TEXAS 79702	
4. Well Location Unit Letter D : 989 Feet From The WEST Line and 660 Feet From The NORTH Line Section 36 Township 17 SOUTH Range 34 EAST NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-4006', RB-4018, KB-4011	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUD 14 3/4" Hole @ 7:30pm 11-20-89. BASIN Rig 10.
TD 14 3/4" @ 4:11am 11-21-89 RAN 37 ft. of 11 3/4", 42 #, H-40, ST+C CASING. SET AT 1555'. WESTERN CEMENTED WITH 1300 SACKS CLASS "H" WITH 2% CaCl₂, 1/4 # FLOCELE MIXED AT 15.6 ppg. CIRCULATED 207 SACKS.
TESTED CASING TO 1000 PSI FOR 30 MINUTES
DRILLING.
Plug down 1 3/4" @ 11-23-89
DRILL cut 6 PM 11-24-89

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE **C.P. Basham** TITLE **Drilling Superintendent** DATE **12-5-89**
(915)
TYPE OR PRINT NAME **C.P. BASHAM** TELEPHONE NO. **688-4620**

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE **DEC 11 1989**

CONDITIONS OF APPROVAL, IF ANY: