Form 3160-5 (November 1983) (Formerly 9-331)  DEPARTMENT OF THE INTERIOR (Other Instructions on re- BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT-" for such proposals.)						Form approved.  Budget Burcau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO  NM 0392867  6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
2. NAME OF OPERATOR						8. FARM OR LEASE NAME		
Santa Fe Energy Operating Partners, L.P. 3. ADDRESS OF OPERATOR						Uncle Sam 13 Federal 9. Wall No.		
500 W. Illinois, Suite 500, Midland, TX 79701  1. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface						10. FIELD AND POOL, OR WILDCAT		
990' FNL & 1980' FEL, Sec. 13. T-18S, R-32E						West Corben Delaware 11. SEC., T., E., M., OR BLE. AND SURVEY OR ARMA		
14. PERMIT SO. 15. ELEVATIONS (Show whether DF, RT, CR, etc.)						Sec. 13, T-18S, R-32E		
	2I #30-025-30732 3848.6' GR					12. COUNTY OR PARISH 13. STATE		
16.		A D T			Lea		NM	
		TENTION TO:	ingicate ivo	ature of Notice, Report, o				
TEST WATER			[]		SEQUENT REPORT OF:		<del></del>	
FRACTURE T	REAT	MULTIPLE COMPLETE ABANDON®		WATER SHUT-OFF FRACTURE TREATMENT	ALTE	RING WELL		
REPAIR WEL		CHANGE PLANS		shooting or acidizing (Other) Set csg	string	DONMENT*	$-\frac{1}{x}$	
(Other) 17. DEFERTBLE PRO- proposed - nent to thi		OPERATIONS (Clearly states)	te all pertinent ubsurface location	(Norm: Report rest	ults of multiple companies of multiple companies and	Log form.)	eli	
12-19-89:	Drilled to FC at 8726'	8816' (TD). R and DV tool a	an 206 jts t 5186'.	s 5-1/2" 17# N-80 c	casing and se	et at 88	16'.	
12-20-89: Cemented as follows: 1st stage - pumped 10 Bbls sure bond followed by 1250 sx Cl H w/ 5% salt & 1% CF-1, 15.7 ppg. Displaced w/ fresh water. Drop bomb, open DV tool. Circ 30 sx off of DV tool from 1st stage. 2nd stage - 1080 sx Pacesetter lite w/ 10# salt, 12.5 ppg followed by 525 sx Cl H, 5% salt, 1% CF-1, 15.7 ppg. Displaced w/ fresh water. PD at 12:26 p.m. MST. Circ. 133 sx. Set slips w/ 140,000#. Cut off 5-1/2". NU wellhead and test to 2000 psi. Jet and clean pits. Rig released at 8:30 p.m. MST on 12-20-89. WOCU.								
				occircity occur	te (j. 1949)			
				occurry our	<b>&gt;</b>			
				july 1 de		(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	·	
				CARLSB4U		71 (2) <b>64</b>	RECEIV	
		g is true and correct				- 12 V	<del>- m</del>	
SIGNED #	1544 1(C)	ullough	TITLE Sr.	Production Clerk	DATE	12-26-89	)	
(This space f	or Federal or State	office use)	<del></del>		-			
APPROVED CONDITIONS	BY B OF APPROVAL, II	ANY:	TITLE		DATE			

HOBBS OF CE