

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL  
(Other instructions  
verse side)

TE  
re

Form approved  
Budget Bureau No. 1-1-1  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Harvey E. Yates Company		8. FARM OR LEASE NAME Chevron 12 Federal
3. ADDRESS OF OPERATOR P.O. Box 1933, Roswell, New Mexico 88202		9. WELL NO. #6
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FNL & 660' FEL		10. FIELD AND POOL, OR WILDCAT North Young - Bone Spring
14. PERMIT NO. 30-025-30740		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 12, T18S, R32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3886.6 GL		12. COUNTY OR PARISH Lea
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENTS

(Other) Spud, Surface & Interm. csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/5/89 Spud well @ 1:15 pm  
TD 17 1/2" hole @ 350'; Ran 350' 13 3/8 csg  
Cmtd w/375 sks "C" w/2% CaCl & 1/4# floceal  
Circ 94 sks to pit, WOC 12 hrs, Test BOP 600 psi/30 min-Held ok

12/9/89 TD 12 1/4" hole @ 2935', Ran 2935' 8 5/8 csg  
Cmtd w/1100 sks filler & 200 sks "C"  
Circ 32 sks to pit, WOC 12 hrs, Test BOP 1200 psi/30 min-Held ok

18. I hereby certify that the foregoing is true and correct

SIGNED

NM Young

TITLE

Drilling Superintendent

DATE

12/28/89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

1-5-90

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

JAN 11 1990

OCO  
MOBBS OFFICE