

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30786
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling	7. Lease Name or Unit Agreement Name R.E. Graham 7
2. Name of Operator Helmerich & Payne, Inc.	8. Well No. 5
3. Address of Operator 5401 S. Hattie - Oklahoma City, OK 73129	9. Pool name or Wildcat <i>North Young Wildcat</i>
4. Well Location Unit Letter <u>K</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>1910</u> Feet From The <u>West</u> Line Section <u>7</u> Township <u>18S</u> Range <u>32E</u> NMPM <u>Lea</u> County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR - 3775.7

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <u>Set 8 5/8" casing</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 11" hole to 3103'. Set 8 5/8" 32# K-55 STC casing @ 3103'. Cemented w/675 sx Halliburton lite w/15 % salt. Tailed in w/200 sx premium w/2 % CC. Circulated 45 sx cement to surface. Plug down @ 2115 hours, 02/13/90. W.O.C., cutoff casing, weld on head, and NU B.O.P.'s. Test casing to 1500 psi for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roger G. Bureau TITLE Drilling Superintendent DATE 02/14/90
TYPE OR PRINT NAME Roger G. Bureau (405) 677-0206 TELEPHONE NO.

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

FEB 20 1990

RECEIVED

FEB 19 1990

OCD
HOBBS OFFICE