

PROPOSED DRILLING FLUID PROGRAM

0 - 350'

Spud mud consisting of AQUAGEL flocculated with Lime. Use ground paper for seepage loss of fluid and KWIK-SEAL, FIBERTEX and Cottonseed Hulls for severe or total loss.

If total loss of circulation occurs, we suggest mixing two or three 150-200 barrel pills of viscous AQUAGEL/Lime mud treated with 10-15 ppb KWIK-SEAL and/or Cottonseed Hulls. If this does not regain circulation, we suggest drilling to casing point without returns and spotting a similar pill on bottom prior to logging and running casing.

350 - 2,950'

Drill out with brine water and treat with CON DET and BEN-EX/MF-1 to flocculate solids. Circulate controlled section of the reserve pit. Use ground paper for seepage loss. Use pre-hydrated AQUAGEL or ZEOGEL/paper slugs as needed to sweep hole. For corrosion control, use Sodium Bichromate.

2,950 - 9,400'

Drill out with fresh water or cut brine circulating a controlled section of the reserve pit using BEN-EX/MR-1 and CON DET for control of solids build up. The fluid weight in this interval should be 8.5 - 9.5 pph. Use ZEOGEL/ground paper or pre-hydrated AQUAGEL pills to sweep the hole free of cutting when needed and prior to trips. Use Lime for a 9.0 - 9.5 pH. Use Sodium Bichromate at 600-800 ppm concentration for drill pipe and casing corrosion control.

The addition of MR-1/BEN-EX and CON DET may be used for control of solids build up. Use ZEOGEL/ground paper sweeps for seepage and additional hole cleaning. Should abnormal pressures be encountered in the Strawn formation an early mud up may be necessary.

Exhibit C
Santa Fe Energy Operating Partners, LP
Corrienta 12 Federal No. 1
Section 12-18S-32E
Lea County, New Mexico