

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

WATER CONSERVATION COMMISSION
HOBBY NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Morexco, Inc.

3. Address and Telephone No.

P. O. Box 481, Artesia, NM 88211-0481

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 7: T18S, R32E
2310' FNL & 1650' FEL
SW/4NE/4, Unit Letter G

5. Lease Designation and Serial No.

NM-40449

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Young North 7 Fed. #1

9. API Well No.

30-025-30897

10. Field and Pool, or Exploratory Area

~~undesignated~~ *Pearse!*
Queen

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☒ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug back and recompletion went as follows: (work occurred 7/21 - 7/31/95)

1. Set CIBP and tag CIBP @ 9585' and dumped 35' of cement on top.
2. Spotted 9½# mud from 9550' - 4010'.
3. Spotted 25 sxs plug from 6344' - 6091'.
4. Spotted 25 sxs plug from 4264' - 4010'.
5. Perf. 5½' casing from 3704' - 3714'.
6. Acidized perfs with 1000 gals of 15% NEFE acid.
7. Fraced perfs with 18,000 gals of x-link 40# gelled 2% kcl water with 44,500# of 16/30 mesh sand.
8. Ran tubing to a depth of 3774' open ended and ran pump & rods to recover load.

Will file completion report at later date.

RECEIVED FOR RECORD
J. Lee

14. I hereby certify that the foregoing is true and correct

Signed *Khonda Q. Becker* Title Agent

Date 8-7-95

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

RECEIVED

AUG 5 3 1935

OLD BRIDGE
OFFICE