

WRS COMPLETION REPORTCOMPLETIONS SEC 20 TWP 17S RGE 37E
PI# 30-T-0013 10/12/90 30-025-30906-0000 PAGE 1NMEX LEA * 330FNL 1980FWL SEC NE NW
STATE COUNTY FOOTAGE SPOT
LYNX PET CONSULTANTS C D DO
OPERATOR WELL CLASS INIT FIN

1 SHIPP E D FEE

WELL NO. 3773GR LEASE NAME MIDWAY
OPER ELEV FIELD/POOL/AREA

API 30-025-30906-0000

LEASE NO. PERMIT OR WELL I.D. NO.

06/21/1990 08/26/1990 ROTARY VERT OIL
SPUD DATE COMP. DATE TYPE TOOL HOLE TYPE STATUS

5500 SN ANDRS PETERSON DRLG 3

PROJ. DEPTH PROJ. FORM CONTRACTOR

DTD 5220 PB 5174 FM/TD SN ANDRS

DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

4 MI NW HUMBLE CITY, NM

WELL IDENTIFICATION/CHANGES

OPER CHGD FROM OSBORN HEIRS

CASING/LINER DATACSG 8 5/8 @ 404 W/ 250 SACKS
CSG 5 1/2 @ 5220 W/ 275 SACKS**TUBING DATA**

TBG 2 3/8 AT 5152

INITIAL POTENTIALIPP 10BOPD 20BW 24HRS
SN ANDRS PERF W/ 16/IT 5104- 5112
GTY 36.0 GOR TSTM

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	RUSTLER		2064	1709		
LOG	SALT		2163	1610	3154	619
LOG	YATES		3280	493		
LOG	QUEEN		4266	-493		
LOG	GRAYBURG		4736	-963		
LOG	SN ANDRS		5008	-1235		

CONTINUED IC# 300257017990

Copyrighted 1990
Reproduction
Prohibited**Petroleum Information**PI-WRS-GFT
Form No 187**DB** a company of
The Dun & Bradstreet Corporation

COMPLETIONS SEC 20 TWP 17S RGE 37E
 PI# 30-T-0013 10/12/90 30-025-30906-0000 PAGE 2

LYNX PET CONSULTANTS D DO
 1 SHIPP E D FEE

TYPE FORMATION LTH TOP DEPTH/SUB BSE DEPTH/SUB
 SUBSEA MEASUREMENTS FROM GR

PRODUCTION TEST DATA
 SN ANDRS PERF W/ 16/IT 5104- 5112
 PERF 5104- 5112
 ACID 5104- 5112 5500GALS
 15%

LOGS AND SURVEYS /INTERVAL, TYPE/				
LOGS	GR	DLL	ML	
LOGS	SDBL	DSN	CBL	
HOLE DEVIATION /DEPTH, DIRECTION, ANGLE/				
404	.8D	903	.8D	1400
1901	1.0D	2399	1.0D	2896
3395	.8D	3495	.8D	3893
4390	1.3D	4623	1.0D	5120
5220	2.0D			

DRILLING PROGRESS DETAILS

05/15	LYNX PET CONSULTANTS
06/25	BOX 1979
07/02	HOBBS, NM 88241
07/13	505-392-6950
09/10	LOC/1990/
	DRLG 4335
	DRLG 5170
	5220 TD, COMPLETING
	5220 TD, WOPT
10/11	TD REACHED 07/01/90 RIG REL 07/02/90
	5220 TD, PB 5174
	COMP 8/26/90, IPP 10 BO, 20 BWPD,
	GOR TSTM, GTY 36
	PROD ZONE - SAN ANDRES 5104-5112
	NO CORES OR DSTS RPTD