Submit 3 Copies to Appropriate District Office

State of New Mexico

Form C-103 Energy, Minerals and Natural Resources Department Revised 1-1-89 DISTRICT I OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 WELL API NO. P.O. Box 2088 30-025-30967 DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate: Type of Lease FEE | STATE DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 6. State Oil & Gas Lease No. B-1722-1 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) NEW MEXICO -N- STATE Type of Well: METT X OTHER Name of Operator & Well No. TEXACO PRODUCING INC. 10 3. Address of Operator 9. Pool name or Wildcat P. O. Box 3109 Midland, Texas 79702 VACUUM GLORIETA 4. Well Location 990 Feet From The SOUTH 895 Feet From The WEST _ Line and _ Line Section ship 17-SOUTH Range 35-EAST 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 17-SOUTH Township **NMPM** County GR-3990', KB-4003' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB X OTHER: OTHER: PRODUCTION CASING 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1. DRILLED 7 7/8 HOLE TO 6320'. TD @ 10:30pm 01-10-91. 2. SCHLUMBERGER RAN GR-DLL-MLL-CAL & GR-CNL-LDT FROM 6320' TO 3000'. GR-SONIC FROM 6320' TO 3800'. PULLED GR TO SURFACE. 3. RAN 154 JTS OF 5 1/2, 15.5#, K-55, LT&C CASING SET @ 6320'. DV TOOL @ 5009'. 4. HALLIBURTON CEMENTED: 1st STAGE - 350 SACKS CLASS H w/ 1/4# FLOCELE @ 15.6ppg. OPEN DV TOOL @ 11: 00pm 01-12-91. CIRCULATED 50 SACKS. 2nd STAGE - 600 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT & 1/4# FLOCELE @ 12.8ppg. F/B 250 SACKS CLASS H @ 15.6ppg. PLUG DOWN @ 6:00am 01-13-91. CIRCULATED 75 SACKS. 5. INSTALL WELLHEAD & TEST TO 2000#. 6. ND. RELEASE RIG @ 12:00pm 01-13-91. 7. PREP TO COMPLETE. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

C.P. Basham TITLE DRILLING SUPERINTENDENT DATE 01-14-91 TYPE OR PRINT NAME C. P. BASHAM TELEPHONE NO. 915-6884620 (This space for State Use) o del APPROVED BY -