

Form 3160-1
(Jan 1997)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

CHEVRON USA INC.

3. Address and Telephone No.

P.O. Box 1150 Midland TX 79702 ATTN: ED DOHERTY

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980 FSL + 1980 FWL SEC 15 T19S R33E Unit K

5. Lease Designation and Serial No.

NM 36915

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

LOWELL FEDERAL #1

9. API Well No.

30-025-31008

10. Field and Pool, or Exploratory Area

GEM (MORROW)

11. County or Parish, State

LEA NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Drilg + Plugging Summary
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRLU SPUD 14 3/4" hole @ 11:00 AM 11/7/90 DRILG + SURVEY f/O-508 TD 14 3/4" 9:00 PM 11/7/90.
RUN 13 jts 11 3/4" H40 ST+C csq. cmt. w/325 sx "c" circ 20 sx to surface. WOC 42 HRS. tst. WELL HEAD
BOPE. DRILG + SURVEY FROM 509-5200' TD 11" hole @ 2:45 PM 11/19/90. RUN 1095 LDT-CNL
GR-DL-MFL. RUN 125 jts 8 5/8" 32" cmt. w/1750 sx "c" circ 250 sx to surface. Plug down 3:50 AM
11/21/90 Bump plug w/2200#. WOC 30 HRS. tst BOPE + CSQ. OK. DRILG cmt. DRILG + SURVEY
FROM 5201-13700' TD 7 7/8" hole @ 2:00 PM 12/30/90. RUN 1095 DLL-MFL-GR-CNL-LDT.
P & A WELL SPOT 35 sx BALANCED plug f/13700' to 13600' CLASS "H" cmt. Spot plug f/10700-10600'
mix & spot 65 sx CLASS "H" BALANCED plug f/8200-8000'. SET BALANCED plug f/7850-7650'
w/75 sx "c" SET plug f/5300-5100' 65 sx "c" WOC cmt 4 HRS TAG cmt 5109' w/10,000# wt.
SET BALANCED plug f/500-400 w/50 sx "c" SET 50' SURFACE plug. VERBAL APPROVAL SHANNON SHAW 1/3/91

14. I hereby certify that the foregoing is true and correct

Signed E. O. Doherty

Title T. A. Drilg

Date 1/8/91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date 1-14-91