

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31078
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LH 0005
7. Lease Name or Unit Agreement Name STATE -10-
8. Well No. 1
9. Pool name or Wildcat <i>Shipp Strawn</i>
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3762' GR - 3779' RKB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Pennzoil Exploration & Production Co.
3. Address of Operator P.O. Drawer 1828 - Midland, TX 79702-1828	4. Well Location Unit Letter <u>C</u> : <u>810</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>West</u> Line Section <u>10</u> Township <u>17-S</u> Range <u>37-E</u> NMPM <u>Lea</u> County <u></u>

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: TESTING OPNS <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/08/91 Perforate Atoka 11,578'-590' w/4 SPF (49 holes)
2/12/91 Acidized Atoka w/2000 gals Mod-101 w/1000 SCF/BBL N₂ via 2 7/8" tubing.
3/02/91 Attempt to frac Atoka w/17,000 gals Versagel pad & 20,000 gal w/20-40 H.S. Sand - with 1.0 ppg sand on formation job sanded out w/10,142 psi max pressure.
3/16/91 Set C.I.B.P. @ 11,550' w/35' cement.
3/19/91 Perforate Strawn 11324-334, 11342-346, 11351-354 w/2 SPF (37 holes).
3/20/91 Acidized Strawn w/5000 gals 20% NeFe HCL.
4/18/91 Added additional Strawn perfs 11344-11382' w/2 SPF (77 holes).
4/20/91 Acidized Strawn (11524-382 OA) w/5000 gals 20% NeFe HCL.
5/21/91 Shut-in Pending P&A.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF OPERATIONS RULE 1103.02

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Randy M. Hodgins TITLE Senior Petroleum Engineer DATE 06/12/91
TYPE OR PRINT NAME Randy M. Hodgins 915-682-7316
TELEPHONE NO.

(This space for State Use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 14 1991

PL 100-505

JUN 18 1991

100-505