

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31079

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No. V-2526

7. Lease Name or Unit Agreement Name

Kimbrough State

8. Well No. 1

9. Pool name or Wildcat
Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER Dry Hole

2. Name of Operator
BHP Petroleum (Americas) Inc.

3. Address of Operator
5847 San Felipe Ste 3600 Houston, TX 77057

4. Well Location
Unit Letter 0 : 1250 Feet From The South Line and 1725 Feet From The East Line
Section 20 Township 17S Range 31E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3772.5 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The subject well was spud @ 5:30 pm 3/4/91. Drld 17-1/2" hole to 508' KB. Ran 12 jts 13 3/8" 48# H-40 ST&C casing, set @ 504'. Cmt w/525 sx "C". Circ 80 sx to surface. WOC 12 hours. Drilled to 5450'. Ran 22 jts 9 5/8" 53.50# L-80, 34 jts 36# HC-80, 71 jts 36# J-55. Set @ 5436.71'. Cmt w/263 sx. Circ cmt to surface. Drld 7 7/8" hole to TD 12,350'. Ran open hole logs. Set 30 sx "H" open hole plug @ 12,064-160', 200 sx "H" @ 11,212'. Ran DST #1 (Atoka) from 10,942-11,044'. Rec 936' mud, no hydrocarbons. Set 30 sx "H" neat plug from 10,741-10,852', 30 sx "H" @ 9640-9745', 150 sx "H" neat @ 6707-7053'. Drld cmt to 6890'. Spot 300 gal 15% HCL. Ran DST #2 (Glorietta) @ 6760-6890'. Rec 564' drlg fluid and 5264' sulfur water, no hydrocarbons. On 5/3/91 set 30 sx "H" neat 15.6# ppg (Glorietta plug) @ 6820', 35 sx "H" neat 15.6# ppg @ 5493', 40 sx "H" neat @ 1604', 10 sx "H" neat @ surface. Rel rig @ 2:00 am 5/3/91. Cut off cap and put on marker. Well P&A'd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Wayne Kotovsky TITLE Reservoir Engr. DATE 6/26/91

TYPE OR PRINT NAME Wayne Kotovsky Reservoir Engineer TELEPHONE NO. (713) 780-5302

(This space for State Use)

APPROVED BY Lyle F. Turnacliffe TITLE OIL & GAS INSPECTOR DATE JAN 15 '92

CONDITIONS OF APPROVAL, IF ANY:

M P E

RECEIVED

JUL 01 1991