

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-1133
Expires September 30, 1990

MAR 28 10 23 AM '91

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
NM 0141013

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

8. Well Name and No.

Phyllis Federal #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Quail Ridge Bone Springs

11. County or Parish, State

Lea Co., NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hondo Oil & Gas Company

3. Address and Telephone No.

P. O. Box 2208, Roswell, NM 88202 (505)625-6732

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FEL; Sec.20-T19S-R34E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

Perforated, squeezed, acidized & frac'd

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Perforated 10,205' to 10,206' 4 holes, squeezed w/ 100 sx Class "H" cmt.

Perforated Bone Springs w/ 2 JSPF from 10,168' to 10,180' treat w/ 1500 gals 15% NeFe acid, ISIP 2300 psi.

TIH w/ 5 1/2" Alpha CIBP 12000# & set @ 10,100'. Perforate 1 JSPF 5 1/2" csg @ 9517', 9519', 9522', 9528', 9532', 9536', 9541', 9549' total of 8 holes. Dumped 12' cmt on top CIBP @ 10,100' PBTD = 10,088'.

Acidized 5 1/2" csg perms from 9517' to 9549' w/ Dowell using 2000 gals 10% HCL & 1/2% HF + 16 7/8" BS, ISIP 2700 psi.

Frac'd Bone Springs Sand perms 9517'-9549' w/ 10,000 gals prepad & 44,000 gals gelled 3% HCL & 1/4% HF, 2% KCL water & 44,000# 16/20 Carbo-Lite.

14. I hereby certify that the foregoing is true and correct

Signed E. L. Buttross Jr.

Title Petroleum Engineer

Date 03/26/91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

