

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-31190
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Kimbrough
8. Well No.	3
9. Foot name or Wildcat	Levington (Paddock)
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3806.3' (unprepared)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator PHILLIPS PETROLEUM COMPANY	
3. Address of Operator 4001 Penbrook St., Odessa, TX 79762	
4. Well Location Unit Letter E : 660 Feet From The West Line and 1830 Feet From The North Line Section 7 Township 17-S Range 37-E NMPN Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3806.3' (unprepared)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPERATIONS ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/23/91 MI & RU L & M drilling rig. Spud 12-1/4" hole.
5/24/91 Ran 44 jts. 8-5/8" 24# J-55, ST&C casing & set @1841'. Cemented w/1200 sk Class C, 2% CaCl, 14.8 ppg, 1.32 yield, 6.3 gal./sk. Circ. 186 sk to surface.
5/25/91 WOC 18 hrs. Drilling 7-7/8" hole.
6/3/91 Reached TD of 6350'. Ran DLL/MSFL/GR/Cal.; CNL/LDT/GR/Cal-PE; CNL/GR/Cal.
6/4/91 Ran 151 jts. 5-1/2" 15.5#, J-55, LT&C casing & set @ 6350'. DV tool @ 4009'. Cemented w/600 sacks C, 1.1% yield, 14.8 ppg, 6.3 gal./sk 1st stage. Circ. 35 sk to surface. Second stage - 1100 sacks Class C 64/35 POZ 6% gel., 5% salt, 13.2 ppg, 1.7 yield, 8.8 gal./sk, 150 sacks C Neat, 14.8 ppg 1.32 hield, 6.3 gal./sk, 14.8 ppg, Circ. 75 sacks to surface. WOC 18 hrs. Release rig.

Temp. drop from report pending completion activity.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supervisor, Regulation & Proration DATE 6/5/91
TYPE OR PRINT NAME (915) 368-1411 TELEPHONE NO.

(This space for State Use)

APPROVED BY TITLE DATE JUN 07 1991

CONDITIONS OF APPROVAL, IF ANY: