

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1912	T. Canyon	
T. Salt	2076	T. Strawn	
B. Salt	2977	T. Atoka	
T. Yates	3023	T. Miss	
T. 7 Rivers	3269	T. Devonian	
T. Queen	3680	T. Silurian	
T. Grayburg	4368	T. Montoya	
T. San Andres	4579	T. Simpson	
T. Glorieta	5927	T. McKee	
T. Paddock	6022	T. Ellenburger	
T. Blinberry		T. Gr. Wash	
T. Tubb		T. Delaware Sand	
T. Drinkard		T. Bone Springs	
T. Abo		T.	
T. Wolfcamp		T.	
T. Penn		T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo		T. Penn. "B"	
T. Miranda-Fruitland		T. Penn. "C"	
T. Pictured Cliffs		T. Penn. "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Otzie	
Base Greenhorn		T. Granite	
T. Dakota		T.	
T. Morrison		T.	
T. Todilto		T.	
T. Entrada		T.	
T. Wingate		T.	
T. Chinle		T.	
T. Permian		T.	
T. Penn "A"		T.	

TD 6800

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	200	200	Caliche and Shells				
200	350	150	Red Beds				
350	1912	1562	Sandstone & Shale				
1912	2076	164	Anhydrite				
2076	2977	901	Salt				
2977	3023	46	Sandstone-Salt				
3023	3269	246	Sandstone-Siltstone				
3269	3680	411	Sandstone-Siltstone				
3680	4368	688	Sandstone-Siltstone				
4368	4579	211	Lime				
4577	5927	1348	Dolomite				
5927	6022	95	Dolomite-Siltstone				
6022	6800	778	Dolomite				
Total Depth 6800							