

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Envi Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31373
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. E-1190

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☒ OTHER _____		7. Lease Name or Unit Agreement Name Little Maggie AJN State		
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER _____				
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471		8. Well No. 1		
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Pool name or Wildcat Young Strawn		
4. Well Location Unit Letter <u>I</u> : <u>2310</u> Feet From The <u>South</u> Line and <u>990</u> Feet From The <u>East</u> Line Section <u>16</u> Township <u>18S</u> Range <u>32E</u> NMPM Lea _____ County _____				
10. Date Spudded 10-27-91	11. Date T.D. Reached 12-7-91	12. Date Compl. (Ready to Prod.) Dry - P & A 5-5-93	13. Elevations (DF & RKB, RT, GR, etc.) 3875' GR	14. Elev. Casinghead
15. Total Depth 12038'	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools 0-12038'	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name				20. Was Directional Survey Made No
21. Type Electric and Other Logs Run CNL/LDT; DLL				22. Was Well Cored No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"		38'	26"	Redi-Mix	
13-3/8"	54.5#	355'	17 1/2"	375 sx	
8-5/8"	32#	2935'	12 1/2"	1450 sx	
5 1/2"	17#	12038'	7-7/8"	2350 sx	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					27. ACID SHOT FRACTURE CEMENT, SQUEEZE, ETC.		

26. Perforation record (interval, size, and number) SEE ATTACHED PAGE	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	SEE ATTACHED PAGE	

PRODUCTION

28. Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump) Dry				Well Status (Prod. or Shut-in) Dry	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.)						Test Witnessed By	

30. List Attachments

DST'S, Deviation Survey, Logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Rusty Klein Printed Name Rusty Klein Title Production Clerk Date 10-8-93

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>RUSTLER-1128</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>11546</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>3831</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta <u>PENROSE-4102</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand <u>5368</u>	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs <u>6632</u>	T. Entrada _____	T. _____
T. Abo _____	T. 1st Bone Spr Sd <u>8191</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>10298</u>	T. 2nd Bone Spr Sd <u>8868</u>	T. Chinle _____	T. _____
T. Penn _____	T. 3rd Bone Spr Sd <u>9579</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. LWR Leonardian <u>9910</u>	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface	5940	6540	600	SS
40	155	115	Redbeds	6540	6660	120	SS, LS
155	1212	1057	Anhy	6660	7610	950	LS
1212	2600	1388	Salt, Anhy	7610	8000	390	Sh, LS
2600	2700	100	Anhy, Sh, salt	8000	8186	186	Sh, Dolo
2700	2790	90	Salt, Sh, anhy	8186	8450	264	SS, Dolo
2790	3070	280	Anhy, Sh, Dolo, Salt	8450	8520	70	Dolo
3070	3360	290	Anhy, Dolo, Sh	8520	8800	280	LS, Dolo
3360	3860	500	Dolo, Anhy	8800	8880	80	LS
3860	3872	12	SS	8880	9010	130	Dolo, SS
3872	4310	438	Dolo, Anhy	9010	9470	460	SS, LS, Dolo
4310	4500	190	Dolo, Anhy, SS	9470	9750	280	SS, Dolo
4500	4570	70	Dolo, Sd	9750	9880	130	SS, Dolo,
4570	4680	110	Dolo, Anhy	9880	10250	370	LS, Dolo
4680	4960	280	Dolo, SS, Anhy	10250	10300	50	Cht, Dolo
4960	5380	420	Dolo, Anhy	10300	10730	430	Sh, LS, Dolo
5380	5580	200	SS, LS, Dolo	10730	11930	1200	Sh, LS
5580	5760	180	SS	11930	12038	108	Sh, LS, SS
5760	5940	180	SS, Dolo				