

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31395
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2046
7. Lease Name or Unit Agreement Name Moonshine State Unit
8. Well No. 1
9. Pool name or Wildcat Wildcat Bone Springs
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3784' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
YATES PETROLEUM CORPORATION
3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter C : 990 Feet From The North Line and 1650 Feet From The West Line
Section 10 Township 19S Range 36E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11" hole 10-9-91. Ran 97 joints 8-5/8" 32# HC-80 and J-55 ST&C casing set 4001'. Float shoe set 4001', float collar set 3956'. Cemented w/1050 sx Pacemaker Lite "C" + 1/4#/sx Celloseal + 8#/sx Salt (yield 1.97, wt 12.4). Tail in w/200 sx "C" + 1% CaCl2 (yield 1.97, wt 12.4). PD 7:30 PM 10-9-91. Bumped plug to 2250 psi, released pressure and float held OK. WOC. Drilled out 10:15 AM 10-11-91. WOC 14 hrs and 45 minutes. NU and tested to 1500 psi for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-11-91
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: