

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. <b>30-825-31438</b>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name <b>Anschutz-Arco</b>
2. Name of Operator <b>Rand Oil &amp; Gas, Inc.</b>	8. Well No. <b>1</b>
3. Address of Operator <b>1110 N. Big Spring, Midland, TX 79701</b>	9. Pool name or Wildcat <b>South Knowles Devonian</b>
4. Well Location Unit Letter <b>K</b> : <b>1980</b> Feet From The <b>South</b> Line and <b>1980</b> Feet From The <b>West</b> Line Section <b>18</b> Township <b>17S</b> Range <b>39E</b> NMPM County <b></b>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <b>3662.0' GR</b>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Cut 5-1/2" casing @ 7980' & recover casing.
- 2) Set cement plug @ 7928'.
- 3) Deviate hole w/mud motor.
- 4) Drill to total depth of 12,152'.
- 5) Log well.
- 6) Set 5-1/2" casing to total depth. Cmt w/850 sx 50-50 Pozmix.
- 7) Drill out 12,160'
- 8) Acidize w/2000 gals 7-1/2%.
- 9) Stressfrac open hole.
- 10) Acidize w/10,000 gals 15% HCL.
- 11) Swab dry.
- 12) Drill to 12,190'.
- 13) Acid open hole w/10,000 gals 15% acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jeff Rand TITLE President DATE 4/11/94  
TYPE OR PRINT NAME Jeff Rand TELEPHONE NO. 214-788-4960

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 18 1994  
CONDITIONS OF APPROVAL, IF ANY: