N.M. Oi ons. Division

Form 3160-5 (June 1990)	BUREAU OF LAND MANAGEMENT		Hobbs, NM 88241	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM-17807
Do not use this for	SUNDRY NOTICES AND m for proposals to drill or e "APPLICATION FOR PER	to deepen or reentry to	a different reservoir	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE 1. Type of Well				7. If Unit or CA, Agreement Designation
Coll Gas Well Other 2. Name of Operator Morexco, Inc. 3. Address and Telephone No. P. O. Box 481, Artesia, NM 88211 505-746-6520 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Section 15, Township 18 South, Range 32 East 1980 FSL, 660 FEL				8. Well Name and No. Anadarko Fed. #1 9. API Well No. 30-025-31501 10. Field and Marko Marko Arka Cullind. Queen 11. County or Parish, State Lea County, New Mexico
12. CHECK AF	PPROPRIATE BOX(s) TO	INDICATE NATURE	OF NOTICE, REPORT	T, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION				
	Report	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	,	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) ry proposed work. If well is directionally drilled.

additional holes @ 3914-17 8 holes 2 spf. 6/18/98 Acidized perfs w/ 1000 gals of 7 1/2 NEFE acid. Fraced w/ 404 bbls of 30# x-linked gelled 2% kcl w/ 46,000# of 16/30 sand.

6/17/98 Set CIBP @ 5130 w/35' cement on top. Set CIBP @ 4920 w/35' on top. Perforated

6/19/98 - 7/8/98 Swab tested.

7/10/98 Set pumping unit and began pumping.

Date

(This space for Federal or State office use)

PETROLEUM ENGINEER

President

Tide

7-23-98

Approved by ORIG. SGD.) GARY GOURLEY Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

*See Instruction on Reverse Side 7 11 (-- --