State of New Mexico ' rgy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office						
DISTRICT I	OIL CONSERVATION DIVISION			WELL API NO.		
P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088			30-025-31709			
P.O. Box Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088			5. Indicate Type of Lease	TE 🔯	FEE 🗍	
DISTRICT III_				<u>'' 🖂 </u>	' LJ	
1000 Rio Brazos Rd., Aztec, NM 8741	6. State Oil / Gas Lease No. B-2	2706				
SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name VACUUM GLORIETA WEST UNIT			
1. Type of Well: OIL GAS OTHER INJECTION						
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.			8. Well No. 80			
3. Address of Operator 205 E. Bender, HOBBS, NM 88240			9. Pool Name or Wildcat VACUUM GLORIETA			
4. Well Location	NODT	11 Line and 2442	Foot From The FAST	lina		
Unit LetterG :		H Line and 2442		Line		
Section 36	·	ange 34E NM	IPMLEA	A_COUNTY		
	10. Elevation (Show whether DF, RK	B, RT,GR, etc.) 3997 GR				
11. Check A	ppropriate Box to Indicate Nat	ure of Notice, Report	t, or Other Data			
NOTICE OF INTENTION	ON TO:	SU	JBSEQUENT REPOF	RT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CA	SING		
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPERATION PLUG AND ABANDONMENT				
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB				
OTHER:		OTHER: SQZD	PERFS, ADDED NEW PERFS &	ACIDIZED	\square	
 MIRU. RELEASED INJ PKR & TOH W/ INJ EQUIP. SET CEMENT RETAINER @ 5859'. SQUEEZED PERFS FROM 5959'-6159' W/ 75 SACKS CLASS H CEMENT. WOC. TAGGED CMT @ 5840', DRILLED OUT CMT & CMT RETAINER @ 8535' & CEMENT TO 6187', CIRC HOLE CLEAN. TIH W/ WS TO 6176', SPOTTED 75 SACKS CLASS H CMT. WOC. TAGGED CMT @ 5591', DRILLED OUT CMT TO 6070' (NEW PBTD) PERFORATED W/ 2 JSPF FROM 5930'-5968' & 5980'-6020' (.47" HOLES, 78', 156 HOLES). TIH W/ TREATING PKR & SET @ 5810'. ACIDIZED NEW PERFS 5930'-6020' W/ 4000 GALS 15% NEFE. MAX P = 3500#, AIR = 3.5 BPM. SI 1 HR. SWABBED BACK LOAD. TOH W/ PKR. TIH W/ 5 12' BAKER LOC-SET INJ PKR ON 180 JTS 2 3/8" RICE DUOLINED INJ TBG. CIRCD HOLE W/ CORROSION INHIBITED FRESH WATER, SET PKR @ 5845'. TESTED CASING FROM SURFACE TO PKR SET @ 5845' AS PER NMOCD GUIDELINES TO 580# FOR 30 MIN, HELD OK. (ORIGINAL CHART ATTACHED, COPY OF CHART ON BACK) RETURNED WELL TO INJECTION. OPT 7/3/97 INJECTING 1097 BWPD @ 26 PS (INTERNAL TEPI STATUS REMAINS INJ) 						
WITERIAL TERISTATUS REMAINST	ivo)					
SIGNATURE Lowk Care		Asst	DATE	7/9/97		
TYPE OR PRINT NAME	Monte C. Duncan		Telephone N	lo. 397-04	18	
APPROVED BY	Lerri TITLE OIL	, & GAS HOP.	ECTOR DATE	8-1-97	>	
CONDITIONS OF APPROVAL, IF ANY:	THE STA			chols 12-93 ver 1.0		

DeSoto/Nichols 12-93 ver 1.0