

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-67986

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Xion Federal #2

9. API Well No.

30-025-31793

10. Field and Pool, or Exploratory Area

Young Wolfcamp North

11. County or Parish, State

Lea County, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Manzano Oil Corporation

3. Address and Telephone No.

P.O. Box 2107, Roswell, NM 88202-2107 (505) 623-1996

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL & 330' FEL, Section 18, T18S, R32E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Running casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/09/93 Spud 10:30 p.m. 1/8/93.

1/10/93 Ran 10 jts (368.45') of 13-3/8" J55 64.5# ST&C 8R surface csg w/GS & insert float & 1 centrilizer. Set @ 364'KB. Cemented w/350 sks Class C + 2% CaCl. Plug down 12:45 p.m. 1/09/93. Circ 85 sks. 12 hrs WOC.

1/13/93 Ran 59 jts (2525.21') of 8-5/8" 24# J55 ST&C 8R w/guide shoe, float collar & 4 centrilizers. Set @ 2500'KB. Cemented w/700 sks lite + 15# sks salt - 1/4# F.S. + 200 sks Class C + 2% CaCl. Plug down 3:15 p.m. 1/12/93. Had good circ throughout job but did not circulate cement to surface. Run 1" and tag top of cement @ 782'. Cement through 1" as follows:

1st stage - 100 sks Class C + 2% CaCl

2nd stage - Tag top @ 578' - 100 sks Class C + 2% CaCl

3rd stage - Tag top @ 408' - 100 sks Class C + 2% CaCl

4th stage - Tag top @ 204' - 76 sks Class C + 2% CaCl

Circulate 6 sks to surface.

12 hrs WOC.

RECEIVED
JAN 15 11 15 AM '93
CARE
AREA

14. I hereby certify that the foregoing is true and correct

Signed Alvin Ramey

Title Production Analyst

Date January 14, 1993

(This space for Review or State official use)

Approved by David A. Glass
Conditions of approval, if any:

Title

Date

JAN 19 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations.

*See instruction on Reverse Side

RECEIVED

JAN 22 1993

OCD HOBBS OFFICE