State of New Mexico Form C-103 Submit 3 Copies to Appropriate District Office Energy, Minerals and Natural Resources Department Revised 1-1-89 OIL CONSERVATION DIVISION DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-31844 **DISTRICT II** Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease FEE STATE DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 6. State Oil & Gas Lease No. B-155-6 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" VACUUM GLORIETA WEST UNIT (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: WELL WELL OTHER WATER INJECTION 2. Name of Operator 8. Well No. TEXACO EXPLORATION AND PRODUCTION INC. 96 Address of Operator 9. Pool name or Wildcat P. O. Box 3109 Midland, Texas 79702 VACUUM GLORIETA 4. Well Location : 1427 Feet From The SOUTH 183 Feet From The EAST _ Line and _ 36 Township 17-SOUTH Range 34-EAST NMPM LEA 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3986', KB-4000' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB X X OTHER: PRODUCTION CASING OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 1. DRILLED 7 7/8 HOLE TO 6343'. TD @ 9:45am 03-08-93. 2. HLS RAN GR-DLL-MSFL AND GR-DSN-SDL-CSNG-CAL FROM 6330' TO 4200'. PULLED GR-DSN TO SURFACE. 3. RAN 21 JTS OF 5 1/2, 17#, WC-50 AND 124 JTS OF 15.5#, LTC CASING SET AT 6343'. DV TOOL @ 5021'. 4. DOWELL CEMENTED: 1st STAGE - 280 SACKS CLASS H w/ 1/4# FLOCELE (15.6ppg, 1.18cf/s). OPEN DV TOOL @ 2:15pm 03-09-93. CIRCULATED 20 SACKS. 2nd STAGE - 1000 SACKS 35/65 POZ CLASS H w/ 6% GEL, 5% SALT, 1/ 4# FLOCELE (12.8ppg, 1.94cf/s). F/B 100 SACKS CLASS H w/ 1/4# FLOCELE (15.6ppg, 1.18cf/s). PLUG DOWN @ 10:30pm 03-09-93. DID NOT CIRCULATE CEMENT. 5. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 400'. 6. ND. RELEASE RIG @ 2:30am 03-10-93. 7 PREP TO COMPLETE

mowiedge and belief.	
TITLE DRILLING OPERATIONS MANAGER	DATE 03-15-93
	TELEPHONE NO. 915-6884620
	NGC 27 1933
ти	DATE
	TITLE DRILLING OPERATIONS MANAGER