

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31869 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-1520-1
7. Lease Name or Unit Agreement Name VACUUM GLORIETA WEST UNIT
8. Well No. 27
9. Pool name or Wildcat VACUUM GLORIETA
10. Elevation (Show whether DP, RKB, RT, GR, etc.) GR-4012', KB-4026'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER WATER INJECTION

2. Name of Operator
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator
P. O. Box 3109 Midland, Texas 79702

4. Well Location
Unit Letter I : 2359 Feet From The SOUTH Line and 64 Feet From The EAST Line

Section 26 Township 17-SOUTH Range 34-EAST NMPM LEA

10. Elevation (Show whether DP, RKB, RT, GR, etc.)
GR-4012', KB-4026'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: PRODUCTION CASING <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 6370'. TD @ 5:00 PM 05-20-93.
2. HLS RAN GR-DLL-MSFL, GR-DSN-SDL-CAL FROM 4370' TO 6368'. PULLED GR-DSN TO SURFACE.
3. RAN 20 JOINTS OF 5 1/2, 17#, WC-50 AND 124 JTS OF 15.5#, LTC CASING SET @ 6370'.
4. DOWELL CEMENTED WITH 1270 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 11:15 PM 05-21-93. DID NOT CIRCULATED CEMENT.
5. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 1700'.
6. ND. RELEASE RIG @ 2:30 PM 05-21-93.
7. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham / SDH TITLE DRILLING OPERATIONS MANAGER DATE 05-24-93

TYPE OR PRINT NAME C.P. BASHAM TELEPHONE NO. 915-6884620

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAY 26 1993