

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31880
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-155-6
7. Lease Name or Unit Agreement Name VACUUM GLORIETA WEST UNIT
8. Well No. 105
9. Pool name or Wildcat VACUUM GLORIETA
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3999', KB-4013'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER WATER INJECTION
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.
3. Address of Operator P. O. Box 3109 Midland, Texas 79702
4. Well Location Unit Letter N : 453 Feet From The SOUTH Line and 1340 Feet From The WEST Line Section 36 Township 17-SOUTH Range 34-EAST NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3999', KB-4013'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: PRODUCTION CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 6231'. TD @ 12:30 AM 05-04-93.
2. HLS RAN GR-DLL-MSFL, GR-DSN-SDL-CAL FROM 6229' TO 4228'. PULLED GR-DSN TO SURFACE.
3. RAN 17 JOINTS OF 5 1/2, 17# WC-50 AND 130 JTS OF 15.5#, LTC CASING SET @ 6231'.
4. DOWELL CEMENTED WITH 1550 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 5:00 AM 05-05-93. CIRCULATED 20 SACKS.
5. ND. RELEASE RIG @ 10:00 AM 05-05-93.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / SDH

TITLE DRILLING OPERATIONS MANAGER DATE 05-07-93

TYPE OR PRINT NAME C.P. BASHAM

TELEPHONE NO. 915-6884620

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 11 1993