Form 3160-3 (December 1990)

(Other instruct reverse side) N. W. Uh. LED STATES

SUBMIT IN TRI

90-025-3200/ Form approved. Budget Bureau No. 1004-Expires: December 31, 1991

	DEPARTMENT OF THE INTERIOR						5. LEASE DESIGNATION AND SERIAL NO.	
BUREAU OF LAND MANAGEMENT						NM - 073240		
	ATION FOR P	ERMIT OFO	BRILI	OR DEEPEN		6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
DRILI TYPE OF WORK DRILI TYPE OF WELL OIL GAB		DELEPTER		NOVE CO. MILITARY	br =	7. UNIT AGREEMENT N		
OIL WELL OTHER OF OPERATOR 20 OF STREET OF STR						8. FARM OR LEASE NAME, WELL NO.		
Kaiser-Francis Oil Company						Crazy Horse 30 Federal		
3. ADDRESS AND TELEPHONE NO.						2		
P.O. Box 21468, Tulsa, 08, 74125 (918) 494-0000						10. FIELD AND POOL, OR WILDCAT		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*) At surface 330' FSL & 990' FWL At proposed prod. sone Same 14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*						Geronimo-Del		
						11. SBC., T., R., M., OR REK. AND SURVEY OR AREA		
								Sec 30, T198
						Approximately 16 miles South of Maljamar, NM		
15. DISTANCE FROM PROPOSED*						OF ACRES ASSIGNED	I NPI	
LOCATION TO NEAREST PROPERTY OF LEASE LINE, FT. 330				320		TO THIS WELL 40		
(Also to nearest drig. unit line, if any) 18. Distance from from to Location* To Nearest Well, drilling, completed, or applied for, on this lease, yr.					20. ROTA	20. ROTARY OR CABLE TOOLS		
						Rotary		
21. RLEVATIONS (Show whether DF, RT, GR, etc.) 3575.1 GR					<u>'</u>	As soon as possible		
		PROPOSED CAS	ING AND	CEMENTING PROGRA	M Secr	etary's Parash	R-111-P Pot	
SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER P	OOT SETTING DEPTH		QUANTITY OF CEMENT			
	3-3/8", H40	48#		450'	_	430 sx CIRCULATE		
	8-5/8", J55	32#		3400 '		1400 sx CIRCULATE		
7-7/8''	7/8" 5 - 1/2", K55 17#		8000 '			1150 sx(tieback200'into 856")		
 Install 300 Drill 12-1/ Test csg to Drill 7-7/8 If hydrocar 6000' and c 	O# BOP & test 4" hole to 34 1500#. " hole to 945 bons are indient lst stage , install well T TO MENTS AND IONS	. O' & run & O' & run el cated, run w/550 sx & lhead, run	set & Lectri & set 2nd s cemen	tc logs. 5-1/2 csg @ stage w/600 sx. at bond log, pe	liate cs 8000' <u>r</u> erforate	sg & cmt w/1400 w/stage collar e and stimulate	at for	
pen directionally, give pertinen								
	1	· Laa	TI.E		oineer	11	10 00	
SIGNED 17/15	on Chiff	TI		Operations En	8-111-61	DATE	-13-92	
(This space for Federal	or State office use)	T		Operations En		UATE	-13-92	
SIGNED 17/15	or State office use)	TI		Operations En			-13-92	

*See Instructions On Reverse Side