

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico
2281

Northwestern New Mexico

T. Anhy	2281	T. Canyon	10747	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn		T. Kirtland-Fruitland	T. Penn. "C"
B. Salt		T. Atoka	11384	T. Pictured Cliffs	T. Penn. "D"
T. Yates	3464	T. Miss	12192	T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian		T. Menefee	T. Madison
T. Queen		T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya		T. Mancos	T. McCracken
T. San Andres	5424	T. Simpson		T. Gallup	T. Ignacio Otzte
T. Gloriera	6820	T. McKee		Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger		T. Dakota	T.
T. Blinebry		T. Gr. Wash		T. Morrison	T.
T. Tubb	8670	T. Delaware Sand		T. Todilto	T.
T. Drinkard		T. Bone Springs		T. Entrada	T.
T. Abo	9378	T.		T. Wingate	T.
T. Wolfcamp		T. WOODFORD	12120	T. Chinle	T.
T. Perm		T.		T. Permian	T.
T. Cisco (Bough C)		T.		T. Perm "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from to
No. 2, from to
No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
5000	5220	220	LM
5220	5320	100	SS/DOL
5320	6210	890	DOL
6210	6810	600	LM
6810	7860	1050	DOL
7860	9260	1400	SS/LM
9260	9400	140	LM/SH
9400	9600	200	LM/DOL
9600	11100	1500	LM/SH
11100	11400	300	SH/LM
11400	12120	920	LM
12120	12190	70	SH
12190	TD	89	LM