

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32058
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-1404
7. Lease Name or Unit Agreement Name East Vacuum Gb/SA Unit Tract 2721
8. Well No. 003
9. Pool name or Wildcat Vacuum Gb/SA
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3934.3 GL (Unprepared)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. Name of Operator Phillips Petroleum Company
3. Address of Operator 4001 Penbrook St., Odessa, Texas 79762	4. Well Location Unit Letter N : 660 Feet From The South Line and 1415 Feet From The West Line Section 27 Township 17-S Range 35-E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3934.3 GL (Unprepared)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Revised csg., cementing, & mud program ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

See attached revised casing, cementing, and mud program. Filed to amend number sacks of cement, slurry composition, and depth in the mud program.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supv., Reg. Affairs DATE 8/13/93
TYPE OR PRINT NAME L. M. Sanders TELEPHONE NO. 915/368-1488

(This space for State Use)

APPROVED BY Orig. Signed by Paul Kautz Geologist TITLE Geologist DATE AUG 17 1993
CONDITIONS OF APPROVAL, IF ANY:

PROPOSED CASING & CEMENTING PROGRAM

EVGSAU 2721-003

8 5/8" 24 lb/ft J-55 Surface Casing Set at 1650' - 12 1/4" Hole:

Circulate to surface with 800 sx of Class "C" + 2% CaCl_2 .

Slurry Weight:	14.8 ppg
Slurry Yield:	1.32 ft ³ /sx
Water Requirement:	6.3 gals/sx

5 1/2" 15.5 lb/ft J-55 Production Casing Set at 4900' - 7 7/8" Hole:

Lead: 500 sx Class "C" 65/35 Poz + 6% Gel + 3% Salt. Desired TOC = Surface.

Slurry Weight:	12.8 ppg
Slurry Yield:	1.85 ft ³ /sx
Water Requirement:	9.9 gals/sx

Compressive Strength
24 hr 468 psi
48 hr 866 psi

Tail: 350 sx Class "C" 50/50 Poz + 0.5% Halad-9 + 1.5% CaCl_2 . Desired TOC = 4000'.

Slurry Weight:	14.6 ppg
Slurry Yield:	1.15 ft ³ /sx
Water Requirement:	5.0 gals/sx

Compressive Strength
12 hr 520 psi
24 hr 1004 psi

PROPOSED MUD PROGRAM

EVGSAU 2721-003

DEPTH	MUD WEIGHT	VISCOSITY	FLUID LOSS	CL PPM	% SOLIDS	ADDITIVES
Surf - 1650'	8.3-9.0 ppg	28-36 sec/1000 cc	-	-	-	Native Solids
1650' - 4900'	10.0 ppg	28-32 sec/1000 cc	-	Saturated	-	Native Solids