## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89

DISTRICT 1 P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION P.O. Box 2088		WELL AM NO. 30-025-32061	
DISTRICT II P.O. Drawer DD, Artesia, NM \$2210  Santa Fe, New Mexico 87504-2088		S. Indicate Type of Lease	
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			STATE X FEE  6. State Oil & Gas Lease No. A-1320
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: OL GAS WELL X WELL	OTHER.		East Vacuum Gb/SA Unit Tract 3229
2 Name of Operator Phillips Petroleum Company			8. Well No. 013
3. Address of Operator 4001 Penbrook Street	Odessa, TX 79762		9. Pool same or Wildcat Vacuum Gb/SA
4. Well Location Unit Letter K : 2000	Feet From The South	Line and 2630	Feet From The West Line
Section 32 Township 17-S Range 35-E NMPM Lea County			
	10. Elevation (Show whether 3961.3'	DF, RKB, RT, GR, etc.)	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
		SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMEN			OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND C		EMENT JOB	
OTHER: OTHER: Set sur		face & production string X	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			
10-09-93 - Notify NMOCD of intent to spud @8:15 a.m. Spud 12-1/2" hole. 10-11-93 - Run 8-5/8" csg., float collar & 37 jts. 8-5/8" 24#/Ft., K-55, ST&C csg. Land csg. @1560', FC @1513'. Cmt. w/800 sxs. Class "C". Circ. 150 sxs. cmt. to surface. WOC. 10-12-93 - Drilling 7-7/8" hole.			
10-16-93 - RU to log, run #1 GS/LSS/DLL/CAL/MG from TD to 2700', GR/LSS/CAL to surface. Run #2 GR/SDL/CAL/DSN TD to 2700', GR/CAL/DSN to surface. Logger TD 4856'.			
10-17-93 - GIH w/5-1/2" float shoe, 1 jt. 5-1/2" csg., float collar & 112 jts. 5-1/2", 15.50#/Ft. K-55, LT&C csg., land csg. @4837', FC @4791'. Pump 650 sxs. Class "C" 65/35 poz. Tail w/350 sxs. Class "C" 50/50 poz. Circ. 10 sxs. cmt. WOC.			
I hereby certify 3:xt the information above is true and complete to the best of my knowledge and belief.  Supv. Regulatory Affairs 10-22-93			
SIGNATURE L. M. SAILE		E Supv. Regul	(915) TELEPHONE NO. 368-1488
(This space for State Use)			
ORIGINAL SIGNED BY JERRY SEXTON			
APTROVED BY DISTRICE	1 SUPERVISOR 111	LE	PO 7 2 7 1983

CONDITIONS OF APPROVAL, IF ANY: