Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL API NO. **3**21-025-3<u>2204</u> 5. Indicate Type of Lease STATE XX FEE

6. State Oil & Gas Lease No. V-2687

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)					
			7. Lease Name or Unit Agreement Name		
1. Type of Well:					
OEL GAS WELL	OTHER [DRY HOLE	IRON HOUSE		
2. Name of Operator	10		8. Well No.		
MARSHALL & WINSTON,	INC. 14187		1		
3. Address of Operator			9. Pool name or Wildcat		
P. O. BOX 50880, MI	DLAND, TX 79710-0880		WILDCAT		
4. Well Location					
Unit Letter H :	2100 Feet From The NORTH	Line and	Peet From The EAST Line		
Section 1	Township 19S	Range 35E	NMPM Lea County		
	//////////////////////////////////////	nether DF, RKB, RT, GR, etc.)	<i>\(\(\(\(\(\(\(\(\(\(\(\(\(\(\(\(\(\(\(</i>		
	//////////////////////////////////////	<u></u>			
11. Che	ck Appropriate Box to Indic	ate Nature of Notice,	Report, or Other Data		
			BSEQUENT REPORT OF:		
NOTICE	7	F3			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLI	NG OPNS. \square PLUG AND ABANDONMENT Σ		
	- -	_	-		
PULL OR ALTER CASING CASING TEST AND CEMENT JOB			CEMENT JOB		
OTHER:		OTHER:			
	Operations (Clearly state all pertinent details	ails, and give pertinent dates, inc	cluding estimated date of starting any proposed		
work) SEE RULE 1103.					

TD 7-7/8" hole at 7132' on 11/9/93. Ran open hole logs from TD to surface. Obtained plugging instructions from NMOCD and set cement plugs as follows on 11/10/93: #1 - 55 sxs from 5500-5400', #2 - 65 sxs from 3500-3400', #3 - 55 sxs from 1900-1800', #4 - 30 sxs from 500-400', #5 - 10' cement plug in top. All cement plugs were Premium Plus "C" Cement. Cut casing off 3' below GL and installed dry hole marker. Cleaned location. Will rehab site as soon as drilling pits dry enough to cover.

I hereby certify that the information	above is true and complete to the best of my kno	wiedge and belief. TITLE Engineer	DATE 11/16/93 915
TYPE OR PRINT NAME TOM	M. BRANDT		TELEPHONE NO. 684-6373
(This space for State Use)	CRILLIAR, SIGNED BY Flacing WINK Flack REP, II		NOV 03 1994
APPROVED BY		TITLE	DATE

CONDITIONS OF AFPROVAL, IF ANY: