

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-32263

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-2317

7. Lease Name or Unit Agreement Name
VACUUM GLORIETA WEST UNIT

8. Well No.
98

9. Pool name or Wildcat
VACUUM GLORIETA

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

1b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DEEP RESER. ☐ OTHER ☐

2. Name of Operator
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator
P. O. Box 3109, Midland, Texas 79702

4. Well Location
Unit Letter P : 937 Feet From The SOUTH Line and 532 Feet From The EAST Line
Section 35 Township 17-SOUTH Range 34-EAST NMPM LEA County

10. Date Spudded 01-15-94 11. Date T.D. Reached 01-23-94 12. Date Compl. (Ready to Prod.) 02-04-94 13. Elevations (DF& RKB, RT, GR, etc.) GR-4007', KB-4021' 14. Elev. Casinghead 4007'

15. Total Depth 6269' 16. Plug Back T.D. 6135' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By Rotary Tools 0 - 6269' Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name 5876' - 5988'; GLORIETA 20. Was Directional Survey Made YES

21. Type Electric and Other Logs Run GR-DLL-MSFL-CSL-CAL, GR-SDL-DSN-CSNG-CAL, GR-CCL 22. Was Well Cored NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	24#	1500'	11	CL-C 650 SX, CIRC. 96 SX	
5 1/2	15.5#	6269'	7 7/8	CL-H 1925 SX, CIRC. 39 SX	

LINER RECORD				TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8	6014'

26. Perforation record (interval, size, and number)
5876-5884, 5898-5904, 5932-5988; 2 JSPF, 140 HOLES.

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5876' - 5988'	ACID: 6000 GAL., 15% HCL

PRODUCTION

28. Date First Production 02-06-94		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING - 2.5 X 1.5 X 24				Well Status (Prod. or Shut-in) PRODUCING	
Date of Test 02-08-94	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 155	Gas - MCF 33	Water - Bbl. 40	Gas - Oil Ratio 213
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.) 38.40	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD Test Witnessed By RANDY TRAMMEL

30. List Attachments
DEVIATION SURVEY

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature C.P. Basham / SDH Printed Name C.P. BASHAM Title DRLG. OPER. MGR. Date 02-11-94

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____	T. Strawn _____
B. Salt _____	T. Atoka _____
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____	T. Montoya _____
T. San Andres _____	T. Simpson _____
T. Glorieta 5812'	T. McKee _____
T. Paddock 5930'	T. Ellenburger _____
T. Blinberry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzite _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 5876' to 5988' No. 3, from to
No. 2, from to No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
5812'	6038'	226'	LIMESTONE				
6038'	6269'	231'	DOLOMITE				