Submit 3 Copies to Appropriate

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

District Office	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATIO P.O. Por 2009	- IWHI APINO
P.O. Box 208 DISTRICT II Santa Fe, New Mexico	87504-2088
P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	5. Indicate Type of Lease STATE X FEE
TOO RE SIEUS RE, RESC, RIN 8/410	6. State Oil & Gas Lease No. 548570
SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF THE PROPOSALS.) DIFFERENT RESERVOIR. USE "APPLICATION FOR PER (FORM C-101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A
1. Type of Well: OIL	THE WILLIAM OF STATE NOTE.
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.	8. Well No. 36
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	9. Pool name or Wildcat VACUUM DRINKARD
4. Well Location	
Unit Letter N : 330 Feet From The SOUTH	Line and 2210 Feet From The WEST Line
Section 36 Township 17-SOUTH Ran	ge 34-EAST NMPM LEA County F, RKB, RT, GR, etc.)
GR-3995', KB-4009'	
11. Check Appropriate Box to Indicate N NOTICE OF INTENTION TO:	ature of Notice, Report, or Other Data
	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB
OTHER:	OTHER: PRODUCTION CASING X
 Describe Proposed or Completed Operations (Clearly state all pertinent details, and work) SEE RULE 1103. DRILLED 7 7/8 HOLE TO 8100'. TD @ 4:45 AM 02-26-94. HLS RAN GR-DLL-MSFL FROM 8100' TO 6000', GR-SDL-DTO SURFACE. RAN 19 JOINTS OF 5 1/2, 17# L-80, 24 JOINTS OF 17# VSET @ 8100'. DV TOOL @ 5013'. DOWELL CEMENTED: 1ST STAGE - 250 SACKS 35/65 POZ PPG, 1.94 CF/S). F/B 225 SACKS CLASS H (15.6 PPG, 1.18 CIRCULATED 92 SACKS. 2ND STAGE - 800 SACKS 35/65 POZ PPG, 1.94 CF/S). F/B 100 SACKS CLASS H (15.6 PPG, 1.18 CIRCULATE CEMENT. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 1000'. ND. RELEASE RIG @ 10:00 PM 02-27-94. PREP TO COMPLETE. 	OSN-CSNG FROM 8100' TO 6000' & GR-DSN FROM 8100' VC-70 AND 145 JOINTS OF 15.5# WC-50. LTC CASING CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 CF/S). OPEN DV TOOL @ 12:00 PM 02-27-94. CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8
I bereby certify that the information above is true and complete to the best of my knowledge and be stonature. Basham / Show Tittle TYPE OR PRINT NAME C.P. BASHAM (This space for State Use)	DRILLING OPERATIONS MANAGER DATE 03-02-94 TELEPHONE NO. 915-688462
APTROVED BY TITULE	ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR DATE