

RECEIVED

OCT 5 8 29 AM '94

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
3. BOX 1980
HOBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No.

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL and 660' FEL (NE/NE) Unit A
Sec. 34, T19S-R34E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-052

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

Mallon 34 Federal #2

9. API Well No.

30-025-32606

10. Field and Pool, or Exploratory Area

Delaware

11. County or Parish, State

Lea, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Casing/Cementing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On September 30, 1994 Mallon Oil Company made TD at 6313' with 7-7/8" bit, ran 5-1/2" x 15.5 # casing to 6312', with DV tool at 3717'.

First Stage: 540 sacks class "C" cement plus 3# Hi-Seal plus 1/8# Cello-Seal plus 12# CSE + 1# WL-1P plus 3/10% CF-2, plug down at 5:30 am, 10/01/94, open DV tool, circulated cement to surface.

Second Stage: 825 sacks class "C" cement plus 3% CF-14 plus 0.5% thrifty lite plus 1/4# cello-seal followed by 50 sacks class "C" plus 0.5% CF-14, plug down at 12:45 pm 10/01/94, good circulation through out both cement stages. October 1, 1994 run temperature log, cement top at 1150' from surface.

17 1994

JU

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 10/05/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side