

L.M. Oil Cons. Division
P.O. Box 1980
Hobbs, NM 88241

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No.

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

4. Location of Well (Footage Sec. T. R. M. or Survey Description)

660' FSL and 990' FEL (SE SE) Unit P
Sec. 27, T19S-R34E

5. Lease Designation and Serial No.
NM-04452

6. Indian, Allote or Tribe Name

N/A

7. Unit or GA Agreement Designation

N/A

8. Well Name and No.

Mallon 27 Federal No. 2

9. Well API No.

30-025-32653

10. Field and Pool or Exploratory Area

NE Lea Delaware

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other: Deepen TD

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

To amend APD to deepen TD to 8300' (Delaware). Estimated tops of important geologic markers: Brushy Canyon 6300', Bone Springs 8300'. Land 9-5/8" csg at 1500' +/- and circulate cement to surface. Drill 8-3/4" hole from 1500' to 8300' with 10 ppg brine water mud system. Logging 8300' to surface (GR, CNL, FDC, DLL, MSFL). Run 5-1/2" x 17# and 15.5# csg from TD to surface, DV tool at 5000' +/- . Two stage cement, cement top 400' inside 9-5/8" csg. Estimated Delaware BHP 2800 psi. There will be no change in BOP equipment and no H2S is anticipated in association with deepening operations.

14. I hereby certify that the foregoing is true and correct.

Signed

Duane C. Winkler

Title

Operations Manager

Date

12-31-96

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

(ORIG. SGD.) ALEXIS C. SWOBODA

Title

Date

JAN 11 1997

Conditions of approval, if any:

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side